

# Working with User Controlled Attributes & Master Data Import

Stratum.Viewer 7



## Getting Started

- [Access To Master Data Import](#)
- [Access To User Controlled Attribute Maintenance](#)
- [Introduction To User Controlled Attributes And Master Data Import](#)
- [Master Data Import Requirements Checklist](#)
- [Master Data Import Initial Setup Checklist](#)

## Tasks

### Setting Up User Controlled Attributes

- [Add A User Controlled Attribute To Stratum](#)
- [Create A Hierarchy Based On A User Controlled Attribute](#)
- [Process User Controlled Attribute Pending Additions/Changes \(Uses Stratum.Connector\)](#)

### Importing Master Data For User Controlled Attributes

- [Specify Upload File Location For Master Data Imports](#)
- [Import Master Data For User Controlled Attributes](#)
- [Adjust Data Mapping And Import Configuration For Master Data Import](#)
- [Delete A Master Data Import](#)

## Additional Information

### Import File Examples & Setup

- [Import Data For Single User Controlled Attribute](#)
- [Import Data For Multiple User Controlled Attributes](#)
- [Tips For Setting Up Your Master Data Imports](#)

### Windows

- [Attributes And Hierarchies Window](#)
- [Data Mapping – Master Data Import Window](#)
- [Import Configuration Window](#)
- [Master Data Import List Window](#)
- [System Configuration Window](#)
- [User Controlled Attribute List Window](#)
- [User Controlled Attribute Maintenance Window](#)

### Advanced Concepts

- [Edit Names Of User Controlled Attributes](#)
- [Edit Names Of Hierarchies And Levels Based On User Controlled Attributes](#)
- [Remove User Controlled Attributes](#)
- [Remove Hierarchies Based On User Controlled Attributes](#)
- [Review History Of Changes For User Controlled Attribute](#)
- [Review Processing Details For A Master Data Import](#)
- [Understanding Your Imported Master Data](#)

- [Using Master Data Import To Add New Dimension Key Values](#)
- [When To Do An Update Vs. When To Do A Replace For Your Master Data Imports](#)

#### **FAQ's**

- [Can I Import Data Into More Than One Attribute At A Time?](#)
- [Can I Import Data Into Corporate Controlled Attributes?](#)
- [Is There A Limit To How Many User Controlled Attributes I Can Set Up?](#)
- [What Does "Import File Contains Key Values That Don't Currently Exist In Stratum" Message Mean?](#)
- [What Happens If I Delete a Master Data Import That's Been Processed?](#)
- [What Should I Do If An Import File Size Exceeds Maximum Allowed Size?](#)
- [Why Can't I Delete A Master Data Import?](#)
- [Why Did I Get An Email About Pending Changes For A User Controlled Attribute?](#)
- [Why Didn't I Get An Email About A Master Data Import After It Finished Processing?](#)
- [Why Didn't The Import Configuration Window Show When I Uploaded An Import File?](#)
- [Why Isn't A User Controlled Attribute Available In My Views?](#)
- [Why Were Some Mapping Selections Made For Me Automatically & Can I Change Selections?](#)

#### **Definitions**

- [Corporate Controlled Attribute](#)
- [Regular Measure Item](#)

- [Target Dimension For Master Data Import](#)
- [User Controlled Attribute](#)

## Getting Started

### Access To Master Data Import

Security and view administrators have full access to Master Data Import functionality. Administrators have access to this functionality from a Master Data Import option in the Analyst Tools menu off of the main menu in Stratum.

Advanced and casual users can access some Master Data Import features if administrators give them direct access to the Master Data Import window – and in that case, they can only work with their own master data imports. The Master Data Import option will not display in the Analyst Tools menu for advanced and casual users, but there are two options for giving access to those types of users. Administrators can set up a global user link that points to the Data Import window and add it to the view groups of the applicable advanced or casual users who need access to Data Import. Or, administrators can send those users a direct URL to the Master Data Import window.

---

**Note:** Master Data Import functionality requires a Stratum Analyst Hub license and is available only for Stratum.Viewer implementations where Stratum.Server is running on a Windows server. It is not available for implementations running Stratum.Server on an IBM i Server.

---

### Access To User Controlled Attribute Maintenance

Security and view administrators have full access to User Controlled Attributes functionality. Administrators have access to this functionality from a User Controlled Attribute option in the Manage Things menu off of the main menu in Stratum.

---

**Note:** User Controlled Attributes functionality is available only for Stratum.Viewer implementations where Stratum.Server is running on a Windows server. It is not available for implementations running Stratum.Server on an IBM i Server.

---

## Introduction To User Controlled Attributes & Master Data Import

User Controlled Attributes gives you the ability to define and populate master data that supplements existing core Stratum data. Add new attributes on-demand that can be used to describe Stratum dimensions and support new levels of data summarization – as done in the example below. A new attribute for the UPC Global Number dimension had a hierarchy created for it, which is then used in the rows of a YTD sales report. Master Data Import is used to update those attributes with current data and is a quick way to add new dimension key values into the Stratum Data Hub. Security built into the Data Hub maintains the integrity of attributes originating from corporate business systems while keeping track of the separate incoming streams of data for User Controlled Attributes.

### User Controlled Attribute Maintenance

General

Dimension: UPC Global Number  
Attributes: **UPC Marketing Promotion**  
Default Value: %  
Create Hierarchy: Yes  
Hierarchy Name: UPC - Marketing Promotion  
Level Name: UPC - Marketing Promotion

Details

Last Updated Date: 10/21/2020 9:24:16 AM  
Last Updated By: Karen Shype  
Reading Updates: No

### Data Mapping - Master Data Import

Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option: Update Validate Configuration Preview of rows 1 - 100

Dimension	Attribute	Attribute	Attribute
UPC Global Number	UPC Seasonal Spend	UPC Shipping Status	UPC Marketing Promotion
UPC Global Number	UPC Seasonal Spend	UPC Shipping Status	UPC Marketing Promotion
0 - 02749 - 25408 - 6	\$6,288.95	Same Day Shipping Available	Back To School
0 - 02749 - 99231 - 6	\$4,189.63	Special Order, Shipping Times Vary	2 For 1
0 - 02749 - 99267 - 6	\$5,458.85	Ship Time > 3 days	50% Off
0 - 06403 - 92736 - 2	\$5,831.04	Back Order	Back To School
		Time > 3 days	Pre-Order Discount
		Time > 3 days	Back To School
		Order	Seasonal - Fall
		Order	Seasonal - Winter
		Same Day Shipping Available	Seasonal - Spring
		Time < 3 days	Seasonal - Summer
		Time < 3 days	Holiday Clearance

### ★ Sales by UPC / Priority Current Month & YTD

View Filter: Division: Multiple

Customer Priority	Current Month Sales This Yr	Current Month Sales Last Yr	Current Month % Change	This Yr Sales YTD	Last Yr Sales YTD	YTD % Change
<b>UPC - Marketing Promotion</b>						
2 For 1	\$40,598,989	\$36,553,845	11.07%	\$481,375,476	\$448,305,198	7.377%
25% Off	\$35,298,234	\$32,116,435	9.91%	\$383,339,152	\$357,637,529	7.187%
50% Off	\$23,005,116	\$19,466,660	18.18%	\$191,354,691	\$175,214,064	9.212%
Back To School	\$54,245,970	\$45,083,567	20.32%	\$493,135,833	\$454,690,324	8.455%
Holiday Clearance	\$23,974,608	\$20,993,153	14.20%	\$280,552,155	\$259,934,157	7.932%
Pre-Order Discount	\$39,440,760	\$35,432,755	11.31%	\$345,809,138	\$319,476,425	8.242%
Rewards Member Discount	\$29,393,584	\$27,216,576	8.00%	\$250,046,229	\$236,743,462	5.619%
Seasonal - Fall	\$15,521,362	\$14,039,051	10.56%	\$152,490,196	\$143,985,943	5.906%
Seasonal - Spring	\$8,921,326	\$8,372,567	6.55%	\$75,574,404	\$71,916,495	5.086%
Seasonal - Summer	\$19,795,805	\$17,074,628	15.94%	\$223,349,148	\$206,516,206	8.151%
Seasonal - Winter	\$28,185,046	\$24,654,149	14.32%	\$236,528,130	\$221,110,766	6.973%

Create Levels From User Controlled Attributes, Add Data To Them With Master Data Imports, & Use Them In Reports

Here's what can you do with User Controlled Attributes:

- **Add Attributes To Complement Corporate Data** – Attributes provide additional descriptive details about your dimensions. Examples are Marketing Promotions and Product Groupings that are controlled and managed outside of your corporate systems.
- **Import Master Data Anytime** – Update or replace data for User Controlled Attributes. In seconds, import master data from Excel spreadsheets. Do so without IT assistance and without waiting for the next scheduled database update.
- **Define New Data Summarizations** – Group data into new analytical categories by creating virtual hierarchies from User Controlled Attributes. This makes the attribute available as a level to use in rows / columns of Viewer reports. See data summarized by attributes via their virtual levels. Use them the same as all other Stratum levels. Drill, filter, build calculations, and more. Master data imported for attributes will

populate their virtual hierarchies. For example, create a Customer Parent roll-up for Customer Sold-To's as an avenue for swiftly linking like customers together.

- **Add New Dimension Key Values** – Master Data Import functionality enhances Budget and Forecasting tasks. Add new key values for items you need to plan on that do not exist yet in corporate business systems. Is there a new Product under development that you need to account for in next year's plan? Include rows with dimension key values in the Excel file for a Master Data Import. The import adds the new key values to Stratum. Then use Viewer's Planning or Data Import to populate the items with budget / forecast measure data.

## Master Data Import Requirements Checklist

A Stratum implementation that uses Master Data Import must meet the following server and software requirements. With these conditions met, administrators can finalize the setup of Master Data Import in Stratum Viewer – see the topic [Master Data Import Initial Setup Checklist](#). Then, Master Data Imports can be added and processed by users.

1. The Stratum.Server application for the implementation must be on a Windows SQL server. Master Data Import is not available for implementations running Stratum.Server on an IBM i Server.
2. Stratum.Connector and Stratum.Viewer must be upgraded to version 7.4 or greater. If they are not, obtain the necessary software and upgrade as you have in the past using the separate install/upgrade guide for instructions.
3. The Stratum.Viewer implementation must have a valid license for the Stratum Analyst Hub. If you don't have the Stratum Analyst Hub, contact your Silvon Sales Representative at (800) 874-5866 or email us at [info@silvon.com](mailto:info@silvon.com). A registration key for a valid license must be specified in the Customer Info and Keys section of the Viewer [System Configuration window](#).

## Master Data Import Initial Setup Checklist

Here's a few things administrators need to do in Stratum.Viewer and Stratum.Connector to prepare Master Data Import functionality for users. After this setup has been completed, users can access Master Data Import features in Stratum.Viewer to add and process their master data imports.

1. **Stratum.Viewer System Configuration Settings** –
  - Verify a registration key is specified in the Stratum Analyst Hub key section of the [System Configuration window](#). Master Data Import is part of the Stratum Analyst Hub.
  - Specify an upload file location for Master Data Imports using the provided field in the Process Options section of the System Configuration window. Copies of import data files are stored in that location. Import files are your Microsoft Excel files that contain imported data. See [Specify Upload Location](#).
2. **Stratum.Connector Parameter Settings** –
  - **Review The “Process Pending User Controlled Attribute Update” Settings** – Properties in that section of the General tab in Connector's Parameter Settings window determine how pending changes for User Controlled Attributes added or edited in Stratum.Viewer are treated by Limited and Standard processes. Setting a process type to No means it won't process any pending changes. Setting a process type to Yes means pending changes will be processed. The process will check for pending changes then switch to a Full process if changes are found so all changes can be processed. See [Connector help](#) for complete details.
  - **Review The “User Controlled Attribute Update Notification” Settings** – Properties in that section of the Email tab in Connector's Parameter Settings window control the email that's sent when a Stratum.Viewer user has added, made changes to, or deleted a User Controlled Attribute. The email tells the recipient that a Full process may be required in Connector to process the change.

3. **Stratum.Connector's Consolidation Writeback Process** --- If you are using Master Data Import and the Planning application to update the Stratum warehouse, make sure that your custom Consolidation Writeback process for Stratum Connector runs the LOADOLAP and CRTOMAST commands.
- Master Data Import allows users to import data for dimension key values that don't exist in a Mast table. When a key value does not exist, then a key value will be added to the UCA Master and MembersN tables.

---



**Note:** The dimension key value is NOT added to the MASTER and MAST tables.

---

- Once the dimension key value is added using Master Data Import, users can add planning data for that key value. This means that there will be transactions in the Planning Writeback tables for key values that don't exist in the Mast table.
- The custom Consolidation Writeback process for Connector needs to run the LOADOLAP and CRTOMAST commands so that any new dimension key values will be properly added to the Mast table.



## Tasks – Setting Up User Controlled Attributes

### Add A User Controlled Attribute To Stratum

1. Click Manage Things then User Controlled Attribute from the main menu in the top panel of Stratum.
2. In the [User Controlled Attribute list window](#), click New User Controlled Attribute .
3. Set up the properties for the new attribute in the [User Controlled Attribute Maintenance window](#).
  - **Dimension** - Choose the dimension to which you want the attribute added.
  - **Attribute** - Enter a name for the attribute.
  - **Default Value** - Specify a character(s) to display as the default value for the attribute. That value will be used for key values that do not yet have data for the attribute. When you see the default value for an attribute in a view, that indicates data does not currently exist for the attribute. For example, if you have not imported data for the attribute using Master Data Import functionality, all key values will be set to the default value. This property defaults to "?" but you can customize it to any text you prefer to use, up to 50 characters.
  - **Create Hierarchy?** - Optionally create a hierarchy based on the new attribute. Creating a hierarchy for it lets you see your data summarized by that attribute by making the attribute available as a level that can be included in rows / columns of a view. "Yes" will create it and enable the name fields below it. You can customize the name of the hierarchy and the level that gets created for it. Names must be different than the attribute on which they are based. The hierarchy and level name default to the name of the dimension for the attribute followed by the name given to the attribute. "No" will skip creating the hierarchy.
4. Save  properties for the new attribute. You are returned to the list window where the addition shows with a Pending Updates status of Yes. The attribute will be added and available in Stratum.Viewer **after** the next Full process occurs in Stratum.Connector. Contact your Stratum administrator for information about when the next Full process is scheduled.

## Create A Hierarchy Based On A User Controlled Attribute

Creating a hierarchy for an attribute lets you see your data summarized by that attribute by making the attribute available as a level that can be included in rows / columns of a view. Data imported into the attribute will populate the hierarchy/level created off the attribute. Use the new level in rows or columns of a view as you would any other level.

1. Click Manage Things then User Controlled Attribute from the main menu in the top panel of Stratum.
2. In the [User Controlled Attribute list window](#), select the attribute you previously added and click Edit .
3. Select "Yes" for Create Hierarchy property when the attribute opens in the [User Controlled Attribute Maintenance window](#).
4. Enter a name for the hierarchy and its level. The names must be different than the attribute on which they are based.
5. Save  the changes. You are returned to the list window where the change shows with a Pending Updates status of Yes. The hierarchy and level will be added and available in Stratum.Viewer **after** the next Full process occurs in Stratum.Connector. Contact your Stratum administrator for information about when the next Full process is scheduled

---

**Note:** Steps above show how to edit an attribute you already added to create a hierarchy from it. You also can create the hierarchy when first adding the attribute. See [Add A User Controlled Attribute To Stratum](#).

---

## Process Pending User Controlled Attribute Additions/Changes (Uses Stratum.Connector)

Adding or changing a User Controlled Attribute is done in Stratum.Viewer. Those additions and changes won't be reflected in Stratum.Viewer until a Full process has been done by Stratum.Connector. A Full process can be scheduled to occur on a regular basis, done in batch, or kicked off manually in Stratum.Connector. Emails configured in Stratum.Connector notify your administrator when Viewer users add or change a User Controlled Attribute. The emails tell the recipients that there are pending changes to process. The timing of when a Full process happens should be done when it won't impact the use of Viewer. Users will not have access to views or most administrator features in Viewer during a Full Process.

See the [Connector help](#) for details about parameters and processes managed in that application.

---

**Note:** See also [Master Data Import Initial Setup Checklist](#).

---

## Tasks – Importing Master Data For User Controlled Attributes

### Specify Upload File Location For Master Data Imports


1. Click Manage Things then System Configuration from the main menu in the top panel of Stratum.
2. Scroll to the Data Imports properties in the Process Options section of the [System Configuration window](#).
3. Use the Master Data Import Upload File Location property to specify the path for the folder that will be used by Master Data Imports. The Master Data Import location is used when importing values into User Controlled Attributes.



- When specifying the location, use the full UNC path format \\host-name\share-name\file\_path\ and include a backslash mark \ as the final character. For example:  
\\serverabc\User Controlled Data\Uploaded Import Files\
- The location must be one that exists already and one to which your implementation's Viewer Impersonation account has access rights.

4. Save  the changes.


## Import Master Data For User Controlled Attributes

1. Click Analyst Tools then Master Data Import from the main menu in the top panel of Stratum.
2. In the [Master Data Import list window](#), click New .
3. When prompted, choose the Excel file to import. Then click Open.
4. Use the [Import Configuration window](#) to select the Target dimension for the import and make other selections that tell Master Data Import about data in the file. The Target dimension has the User Controlled Attributes where imported data is meant to be added, and the selection impacts the attributes available during Step 5.

---

**Note:** Once you have done a few imports, Master Data Import learns about your import data habits and can do some automatic configuration and Data Mapping. When that happens, the Import Configuration window is bypassed. You can open it anytime by clicking the Configuration button in the Data Mapping window.

---

- **Import Option** – Choose Update or Replace. An Update will update existing data and add any new data included in the import file. A Replace clears existing data for **all** of the User Controlled Attributes that belong to the import's Target dimension then adds data from the import file to the applicable attributes. Care should be taken when using a Replace since it removes data for **all** of a dimension's User Controlled Attributes even if the attributes aren't included in the import file. If there is existing data you don't want to lose, then set the import configuration to Update instead of Replace. See also [When To Do An Update Vs. When To Do A Replace For Your Master Data Imports](#).
  - **Target Dimension** – The Target dimension is the one with the attribute(s) that will receive imported data. User Controlled Attributes from that dimension will be available to select when you map imported data to Stratum.
  - **Header Rows In File** – Specify how many header rows are in the import file. Header rows contain descriptive details that aid you in mapping but do not get imported. For example, the row(s) contain dimension names, descriptions, or attribute names.
5. Use the [Data Mapping window](#) to finish telling Stratum what dimensions and attribute data are in the import file. Drop-down lists are provided at the top of the data preview. Use them to make mapping selections.
    - **Ignore** – For any columns you don't want considered, select Ignore.
    - **Dimension** – Choose Dimension for the column that contains the dimension key values, then use the Select A Target drop-down list to select the name of the Target dimension for the data.
    - **Attribute** – Choose Attribute for columns that contain attribute data (values), then use the Select A Target drop-down list to select the name of the Target attribute for the data.
  6. Click the Validate button to check that import data is in the proper format and contains the needed details to proceed.
  7. Master Data Imports are meant to be processed after you are done mapping their data to Stratum. Click the Submit The Master Data Import For Processing  icon. When prompted, confirm that you want to proceed with the process.



## Adjust Data Mapping And Import Configuration For Master Data Import

You can edit an import's mapping and other configuration details at any time while previewing the data.

### Configuration

To adjust general import properties like the Target dimension, click the Configuration button. Use the Import Configuration window to make changes, then click OK.


- **Import Option** – Choose Update or Replace. An Update will update existing data and add any new data included in the import file. A Replace clears existing data for **all** of the User Controlled Attributes that belong to the import's Target dimension then adds data from the import file to the applicable attributes. Care should be taken when using a Replace since it removes data for **all** of a dimension's User Controlled Attributes even if the attributes aren't included in the import file. If there is existing data you don't want to lose, then set the import configuration to Update instead of Replace. See also [When To Do An Update Vs. When To Do A Replace For Your Master Data Imports](#).
- **Target Dimension** – The Target dimension is the one with the attribute(s) that will receive imported data. User Controlled Attributes from that dimension will be available to select when you map imported data to Stratum.
- **Header Rows In File** – Specify how many header rows are in the import file. Header rows contain descriptive details that aid you in mapping but do not get imported. For example, the rows contain dimension names, descriptions, or attribute names.

### Mapping

Use the provided drop-down selection lists in the preview to adjust mapping for each column in the import.

- **Ignore** – For any columns you don't want considered, select Ignore.
- **Dimension** – Choose Dimension for column that contains the dimension key values, then use the Select A Target drop-down list to select the name of the Target dimension for the data.
- **Attribute** – Choose Attribute for columns that contain attribute data (values), then use the Select A Target drop-down list to select the name of the Target attribute for the data.

## Delete a Master Data Import

1. Click Analyst Tools then Master Data Import from the main menu in the top panel of Stratum.
2. In the [Master Data Import list window](#), select the Master Data Import you need to delete.
3. Click Delete .
4. Click Yes in the prompt that displays to proceed with the deletion.

## Import File Setup & Examples

### Import Data For Single User Controlled Attribute

This view contains a "Distribution Partner" User Controlled Attribute that was created for the Customer Parent dimension. This example will show master data being imported to populate the attribute with data.

★ **Sales by Customer Parent**

View Filter: RepBroker: Multiple +

Customer Parent	CPnt Long Description	CPnt Distribution Partner	Actual Sales Amount	Actual Sales Return Amount	Sales After Returns
5000	Wilder Foods	?	\$6,855,423,729	(\$55,695,398)	\$6,711,895,521
5001	Sumpter Distribution	?	\$1,898,425,417	(\$40,429,542)	\$1,864,313,623
5002	Harrington's	?	\$3,009,239,993	(\$38,851,820)	\$2,962,646,046
5003	Good Foods, Inc.	?	\$2,492,017,550	(\$31,720,030)	\$2,454,810,986
6005	Midwest Providers	?	\$435,349,922	(\$9,657,062)	\$428,297,334
6006	Penn Brands	?	\$535,114,379	(\$12,335,779)	\$526,653,133
6007	Oliveri	?	\$804,857,876	(\$18,207,034)	\$789,983,617
6008	Dallas Food Service	?	\$221,068,080	(\$5,618,071)	\$217,432,126
6009	Prestwick Inc	?	\$461,253,044	(\$10,245,029)	\$453,364,978
6010	Smith Inc	?	\$221,735,020	(\$6,203,748)	\$218,010,043
6011	NY Foods	?	\$234,484,912	(\$4,419,089)	\$230,744,232
6012	Montelissi	?	\$182,311,244	(\$5,434,565)	\$179,344,822
6013	Auburn Providers	?	\$190,343,561	(\$6,242,803)	\$187,258,969
6014	Chicagos Finest	?	\$294,095,820	(\$5,974,907)	\$289,540,961
6015	St Louis Dist Inc	?	\$239,053,005	(\$6,713,245)	\$235,189,362
6016	Southwest Inc	?	\$316,841,712	(\$6,139,052)	\$311,737,337
6017	Packingham Corp	?	\$232,102,356	(\$7,639,327)	\$228,392,482
6018	Pacific Corp	?	\$198,442,293	(\$5,269,047)	\$195,262,336
6050	Maple Tree	?	\$200,691,863	(\$6,530,509)	\$197,425,255
6051	Quebec Foods	?	\$263,533,537	(\$4,993,940)	\$259,477,918
6052	Canadian Imports Inc	?	\$241,255,957	(\$7,871,756)	\$237,332,333
6053	Alberta Foods	?	\$224,217,288	(\$5,198,830)	\$220,599,075
Grand Total			\$19,751,858,558	(\$301,390,581)	\$19,399,712,491

An import file containing key values for the associated dimension and master data values for the attribute was set up in Excel. One column has dimension key values while the other has attribute values. A heading row contains names that identify information in the columns, which is helpful to the user when mapping data into Stratum.

Customer Parent	CPrint Long Description	CPrint Distribution Partner
5000	Wilder Foods	Simple & Sophisticated Suppliers
5001	Sumpter Distribution	Sumpter Corp
5002	Harrington's	Organic Specialty Shippers
5003	Good Foods, Inc.	Fresh Food Shipping Distributors
6005	Midwest Providers	Boutique Groups Shipping
6006	Penn Brands	Fine Dining Specialty Products
6007	Oliveri	Earth Care Warehouse Group
6008	Dallas Food Service	Bakers Delivery Services
6009	Prestwick Inc	Fine Dining Specialty Products
6010	Smith Inc	Fresh Food Shipping Distributors
6011	NY Foods	Shoreline Warehouse Services
6012	Montelissi	Sanders & Windley Master Dist
6013	Auburn Providers	Shoreline Warehouse Services
6014	Chicagos Finest	Fine Dining Specialty Products
6015	St Louis Dist Inc	Waylon Dist & Warehouse Group
6016	Southwest Inc	Bakers Delivery Services
6017	Packingham Corp	Organic Specialty Shippers
6018	Pacific Corp	Wholesale Grocers Inc
6050	Maple Tree	Provincial Distribution & Shipping
6051	Quebec Foods	QM Import & Supply
6052	Canadian Imports Inc	QM Import & Supply
6053	Alberta Foods	Provincial Distribution & Shipping

The user initiates the import from the Master Data Import list window.

File Name	Dimension	Owner	Submitted	Completed
Mkt Product Class.xlsx	Product	Mary Leonard	11/12/2020 10:37:36	11/12/2020
Mkt Product Class.xlsx	Product	Mary Leonard	11/12/2020 15:47:27	11/12/2020
new products.xlsx	Product	Mary Leonard	11/12/2020 16:48:01	11/12/2020

After choosing the Excel file for the import, the user provides basic import configuration details including which dimension to use in the import.

**IMPORT CONFIGURATION**

**General**

Import Option:

Target Dimension:

**File Data**

Header Rows In File:

OK Cancel Help

Then, the user maps the import data to Stratum. The mapping window has drop-down lists to define the type of information in each column, where in Stratum to import data from the import file, and which columns, if any, to ignore in the file.

**Data Mapping - Master Data Import**

Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option:

Validate Configuration

Preview of rows 1 - 100

Dimension	Ignore	Attribute
Customer Parent		CPrint Distribution Partner
<b>Customer Parent</b>	<b>CPrint Long Description</b>	<b>CPrint Distribution Partner</b>
5000	Wilder Foods	Simple & Sophisticated Suppliers
5001	Sumpter Distribution	Sumpter Corp
5002	Harrington's	Organic Specialty Shippers
5003	Good Foods, Inc.	Fresh Food Shipping Distributors
6005	Midwest Providers	Boutique Groups Shipping
6006	Penn Brands	Fine Dining Specialty Products
6007	Oliveri	Earth Care Warehouse Group
6008	Dallas Food Service	Bakers Delivery Services
6009	Prestwick Inc	Fine Dining Specialty Products
6010	Smith Inc	Fresh Food Shipping Distributors
6011	NY Foods	Shoreline Warehouse Services
6012	Montelissi	Sanders & Windley Master Dist
6013	Auburn Providers	Shoreline Warehouse Services
6014	Chicagos Finest	Fine Dining Specialty Products
6015	St Louis Dist Inc	Waylon Dist & Warehouse Group
6016	Southwest Inc	Bakers Delivery Services
6017	Packingham Corp	Organic Specialty Shippers
6018	Pacific Corp	Wholesale Grocers Inc
6050	Maple Tree	Provincial Distribution & Shipping
6051	Quebec Foods	QM Import & Supply
6052	Canadian Imports Inc	QM Import & Supply
6053	Alberta Foods	Provincial Distribution & Shipping

Imported data can be used in views as soon as the import completes processing. Here is the view from earlier in the example, showing the “Distribution Partner” User Controlled Attribute populated with the imported master data.


**★ Sales by Customer Parent**

View Filter: RepBroker: Multiple +

<a href="#">Customer Parent</a>	<a href="#">CPrint Long Description</a>	<a href="#">CPrint Distribution Partner</a>	<a href="#">Actual Sales Amount</a>	<a href="#">Actual Sales Return Amount</a>	<a href="#">Sales After Returns</a>
<a href="#">5000</a>	Wilder Foods	Simple & Sophisticated Suppliers	\$6,855,423,729	(\$55,695,398)	\$6,711,895,521
<a href="#">5001</a>	Sumpter Distribution	Sumpter Corp	\$1,898,425,417	(\$40,429,542)	\$1,864,313,623
<a href="#">5002</a>	Harrington's	Organic Specialty Shippers	\$3,009,239,993	(\$38,851,820)	\$2,962,646,046
<a href="#">5003</a>	Good Foods, Inc.	Fresh Food Shipping Distributors	\$2,492,017,550	(\$31,720,030)	\$2,454,810,986
<a href="#">6005</a>	Midwest Providers	Boutique Groups Shipping	\$435,349,922	(\$9,657,062)	\$428,297,334
<a href="#">6006</a>	Penn Brands	Fine Dining Specialty Products	\$535,114,379	(\$12,335,779)	\$526,653,133
<a href="#">6007</a>	Oliveri	Earth Care Warehouse Group	\$804,857,876	(\$18,207,034)	\$789,983,617
<a href="#">6008</a>	Dallas Food Service	Bakers Delivery Services	\$221,068,080	(\$5,618,071)	\$217,432,126
<a href="#">6009</a>	Prestwick Inc	Fine Dining Specialty Products	\$461,253,044	(\$10,245,029)	\$453,364,978
<a href="#">6010</a>	Smith Inc	Fresh Food Shipping Distributors	\$221,735,020	(\$6,203,748)	\$218,010,043
<a href="#">6011</a>	NY Foods	Shoreline Warehouse Services	\$234,484,912	(\$4,419,089)	\$230,744,232
<a href="#">6012</a>	Montelissi	Sanders & Windley Master Dist	\$182,311,244	(\$5,434,565)	\$179,344,822
<a href="#">6013</a>	Auburn Providers	Shoreline Warehouse Services	\$190,343,561	(\$6,242,803)	\$187,258,969
<a href="#">6014</a>	Chicagos Finest	Fine Dining Specialty Products	\$294,095,820	(\$5,974,907)	\$289,540,961
<a href="#">6015</a>	St Louis Dist Inc	Waylon Dist & Warehouse Group	\$239,053,005	(\$6,713,245)	\$235,189,362
<a href="#">6016</a>	Southwest Inc	Bakers Delivery Services	\$316,841,712	(\$6,139,052)	\$311,737,337
<a href="#">6017</a>	Packingham Corp	Organic Specialty Shippers	\$232,102,356	(\$7,639,327)	\$228,392,482
<a href="#">6018</a>	Pacific Corp	Wholesale Grocers Inc	\$198,442,293	(\$5,269,047)	\$195,262,336
<a href="#">6050</a>	Maple Tree	Provincial Distribution & Shipping	\$200,691,863	(\$6,530,509)	\$197,425,255
<a href="#">6051</a>	Quebec Foods	QM Import & Supply	\$263,533,537	(\$4,993,940)	\$259,477,918
<a href="#">6052</a>	Canadian Imports Inc	QM Import & Supply	\$241,255,957	(\$7,871,756)	\$237,332,333
<a href="#">6053</a>	Alberta Foods	Provincial Distribution & Shipping	\$224,217,288	(\$5,198,830)	\$220,599,075
<b>Grand Total</b>			<b>\$19,751,858,558</b>	<b>(\$301,390,581)</b>	<b>\$19,399,712,491</b>

## Import Data For Multiple User Controlled Attributes

Master data can be imported for multiple User Controlled Attributes at that same time, as long as they belong to the same dimension. Here is a view containing two User Controlled Attributes for Ship-To Market. Their default value of “?” shows in the view since no data has been imported yet. This example will show master data being imported to populate both attributes with data.

★ Distribution Sales, Costs by Ship-To Market											
											
View Filter: +											
			Distribution Center Warehouse	Omaha	Omaha	Omaha	Omaha	Charlotte	Charlotte	Charlotte	Cha
Ship-To Market	SMkt Long Description	SMkt Shipping Delay Status	SMkt Order Lead Time	Budget ASP Frozen Current Month/Yr	Sales Units Current Month/Yr	Ext Standard Cost Current Month/Yr	Avg Sell Price Current Month/Yr	Budget ASP Frozen Current Month/Yr	Sales Units Current Month/Yr	Ext Standard Cost Current Month/Yr	Avg Pr Cur Mon
<a href="#">100</a>	Chicago	?	?	\$116,798.68	605,275	\$21,494,231	\$54.09	\$120,702.43	638,721	\$23,484,863	\$!
<a href="#">112</a>	Buffalo	?	?	\$106,426.05	743,410	\$26,955,363	\$52.29	\$101,234.33	722,335	\$27,229,819	\$!
<a href="#">115</a>	Dallas	?	?	\$96,118.53	330,929	\$12,175,833	\$57.86	\$91,420.06	394,384	\$16,533,229	\$!
<a href="#">123</a>	St Louis	?	?	\$100,165.09	948,391	\$36,586,796	\$52.82	\$103,423.02	1,253,709	\$48,131,924	\$!
<a href="#">153</a>	Phoenix	?	?	\$80,774.75	361,809	\$15,080,848	\$64.81	\$85,123.08	363,367	\$13,876,535	\$!
<a href="#">171</a>	Seattle	?	?	\$79,438.39	404,784	\$15,153,515	\$59.29	\$73,925.55	319,200	\$12,799,799	\$!
<a href="#">172</a>	Raleigh-Durham	?	?	\$107,598.23	499,440	\$19,526,501	\$54.66	\$120,964.65	620,669	\$23,630,837	\$!
<a href="#">185</a>	Philadelphia	?	?	\$86,182.52	534,123	\$20,272,073	\$53.87	\$76,619.39	583,375	\$22,553,967	\$!
<a href="#">187</a>	Pittsburgh	?	?	\$43,501.93	103,544	\$4,302,948	\$59.53	\$41,117.40	164,892	\$7,562,591	\$!
<a href="#">207</a>	Quebec QC	?	?	\$94,122.66	581,588	\$22,442,621	\$54.58	\$119,143.34	681,421	\$26,743,905	\$!
<a href="#">229</a>	Calgary AB	?	?	\$93,500.90	580,214	\$20,528,907	\$54.09	\$89,516.86	394,934	\$15,067,517	\$!
<a href="#">249</a>	Winnipeg MB	?	?	\$86,466.49	482,122	\$20,993,451	\$65.64	\$79,527.81	373,263	\$15,318,962	\$!
<a href="#">296</a>	St. John NB	?	?	\$34,772.34	143,679	\$5,655,364	\$68.72	\$33,452.05	121,092	\$4,487,239	\$!
Grand Total				\$1,125,866.55	6,319,309	\$241,168,450	\$56.21	\$1,136,170.00	6,631,362	\$257,421,188	\$!

An import file containing key values for the associated dimension and master data values for the attributes was set up in Excel. One column has dimension key values while the others have attribute values. Two heading rows contain identifying information about the columns, which is helpful to the user when mapping data into Stratum.

	A	B	C	D	E
1			User Controlled Attribute	User Controlled Attribute	
2	Ship-To Market	SMkt Long Description	SMkt Shipping Delay Status	SMkt Order Lead Time	
3	100	Chicago	None	3 business days	
4	112	Buffalo	None	3 business days	
5	115	Dallas	< 1 week	1 week	
6	123	St Louis	None	3 business days	
7	153	Phoenix	1 week	2 weeks	
8	171	Seattle	None	1 business day	
9	172	Raleigh-Durham	None	1 week	
10	185	Philadelphia	< 1 week	3 business days	
11	187	Pittsburgh	1 week	1 business day	
12	207	Quebec QC	None	1 week	
13	229	Calgary AB	None	1 business day	
14	249	Winnipeg MB	1 week	3 business days	
15	296	St. John NB	2 weeks	1 week	
16					
17					
18					

The user initiates the import from the Master Data Import list window.

File Name	Dimension	Owner
UPC Global Number Seasonal Spend Data.xlsx	UPC Global Number	Karen Shype
Customer Priority attributes data.xlsx	Customer Priority	Karen Shype
KEF Customer Parent shipping status.xlsx	Customer Parent	Karen Shype
Customer Parent Shipping Status.xlsx	Customer Parent	Karen Shype

After choosing the Excel file for the import, the user provides basic import configuration details including which dimension to use in the import.

**IMPORT CONFIGURATION**

**General**

Import Option:

Target Dimension:

**File Data**

Header Rows In File:






## Tips For Setting Up Your Master Data Imports

The first step in prepping for a master data import is to collect your data into an Excel file. Familiarize yourself with the following tips and revisit this topic for guidance while setting up import files for Data Imports.

### Save File As “Excel Workbook”


Save your file as an Excel Workbook file type and to a location that you can access while signed onto Stratum.Viewer. Avoid using the Strict Open XML Spreadsheet file type.



## Include Dimension Key Values and Master Data Values

Your import file must include dimension key values and master data values.

- **Target Dimension and Dimension Key Values** – One column needs to contain the import dimension's key values. Use a name at the top of the column that helps you identify the associated Stratum dimension, such as the name that shows up for the dimension in Viewer. Examples of dimensions are Product, Inventory, UPC, and Customer Ship-To.



Customer Ship-To	ShipTo Long Description	User Controlled ShipTo Country	User Controlled ShipTo Title
101116	Harrington's -- Calgary AB	Canada	Purchasing Manager
101116AATQ	Harrington's -- Calgary AB TQA	Canada	Purchasing Manager
101116ACTH	Harrington's -- Calgary AB THA	Canada	Purchasing Manager
101116ADMC	Harrington's -- Calgary AB MCA	Canada	Purchasing Manager
101116AEWO	Harrington's -- Calgary AB WOA	Canada	Purchasing Manager
101116ALAB	Harrington's -- Calgary AB ABA	Canada	Purchasing Manager
101116BATQ	Harrington's -- Calgary AB TQB	Canada	Purchasing Manager
101116BCTH	Harrington's -- Calgary AB THB	Canada	Purchasing Manager
101116BDMC	Harrington's -- Calgary AB MCB	Canada	Purchasing Manager
101116BEWO	Harrington's -- Calgary AB WOB	Canada	Purchasing Manager
101116BLAB	Harrington's -- Calgary AB ABB	Canada	Purchasing Manager
101116CATQ	Harrington's -- Calgary AB TQC	Canada	Purchasing Manager
101116CCTH	Harrington's -- Calgary AB THC	Canada	Purchasing Manager
101116CDMC	Harrington's -- Calgary AB MCC	Canada	Purchasing Manager
101116CEWO	Harrington's -- Calgary AB WOC	Canada	Purchasing Manager
101116CLAB	Harrington's -- Calgary AB ABC	Canada	Purchasing Manager
101116DATQ	Harrington's -- Calgary AB TQD	Canada	Purchasing Manager
101116DCTH	Harrington's -- Calgary AB THD	Canada	Purchasing Manager
101116DDMC	Harrington's -- Calgary AB MCD	Canada	Purchasing Manager

**Note:** If your import contains columns of descriptive info about the dimension that you don't plan to use for the import (such as some of its Corporate Controlled Attributes), you can tell Master Data Import to ignore the columns.

- **Master Data Values For User Controlled Attributes** – Include a column for each User Controlled Attribute where data will be imported. Use a name at the top of each column that helps you identify the associated attribute. If you include columns for more than one User Controlled Attribute, make sure they belong to the same dimension. Imports handle a single dimension at a time.

AutoSave Off Customer ShipTo Country & ShipTo Title 2020-10-15 - Saved

File Home Insert Page Layout Formulas Data Review View Help ACROBAT

D618 Warehouse Supervisor

	A	B	C	D
1	Customer Ship-To	ShpTo Long Description	User Controlled ShipTo Country	User Controlled ShipTo Title
2	101116	Harrington's -- Calgary AB	Canada	Purchasing Manager
3	101116AATQ	Harrington's -- Calgary AB	Canada	Purchasing Manager
4	101116ACTH	Harrington's -- Calgary AB	Canada	Purchasing Manager
5	101116ADMC	Harrington's -- Calgary AB	Canada	Purchasing Manager
6	101116AEWO	Harrington's -- Calgary AB	Canada	Purchasing Manager
7	101116ALAB	Harrington's -- Calgary AB	Canada	Purchasing Manager
8	101116BATQ	Harrington's -- Calgary AB	Canada	Purchasing Manager
9	101116BCTH	Harrington's -- Calgary AB THB	Canada	Purchasing Manager
10	101116BDMC	Harrington's -- Calgary AB MCB	Canada	Purchasing Manager
11	101116BEWO	Harrington's -- Calgary AB WOB	Canada	Purchasing Manager
12	101116BLAB	Harrington's -- Calgary AB ABB	Canada	Purchasing Manager
13	101116CATQ	Harrington's -- Calgary AB TQC	Canada	Purchasing Manager
14	101116CCTH	Harrington's -- Calgary AB THC	Canada	Purchasing Manager
15	101116CDMC	Harrington's -- Calgary AB MCC	Canada	Purchasing Manager
16	101116CEWO	Harrington's -- Calgary AB WOC	Canada	Purchasing Manager
17	101116CLAB	Harrington's -- Calgary AB ABC	Canada	Purchasing Manager
18	101116DATQ	Harrington's -- Calgary AB TQD	Canada	Purchasing Manager
19	101116DCTH	Harrington's -- Calgary AB THD	Canada	Purchasing Manager
20	101116DDMC	Harrington's -- Calgary AB MCD	Canada	Purchasing Manager

ShipTo Master Data

Count: 157

Master Data For User Controlled Attributes (one column per attribute)

## Use Descriptive Info In Header Row(s) To Help Map To Stratum Data

Identifying information about the data contained in each column of your file can be included in the header row(s) of your import file. They help identify what is in each column – saving you time as you map columns or mark them to be ignored while setting up your import. The example shown in the next image uses one header row. You can use more than one header row if needed. All header rows must be located at the top of your file, above the rows of import data.

AutoSave Off Customer ShipTo Country & ShipTo Title 2020-10-15 - Saved

File Home Insert Page Layout Formulas Data Review View Help ACROBAT

D618 Warehouse Supervisor

	A	B	C	D
1	Customer Ship-To	ShpTo Long Description	User Controlled ShipTo Country	User Controlled ShipTo Title
2	101116	Harrington's -- Calgary AB	Canada	Purchasing Manager
3	101116AATQ	Harrington's -- Calgary AB	Canada	Purchasing Manager
4	101116ACTH	Harrington's -- Calgary AB	Canada	Purchasing Manager
5	101116ADMC	Harrington's -- Calgary AB	Canada	Purchasing Manager
6	101116AEWO	Harrington's -- Calgary AB	Canada	Purchasing Manager
7	101116ALAB	Harrington's -- Calgary AB	Canada	Purchasing Manager
8	101116BATQ	Harrington's -- Calgary AB TQB	Canada	Purchasing Manager
9	101116BCTH	Harrington's -- Calgary AB THB	Canada	Purchasing Manager
10	101116BDMC	Harrington's -- Calgary AB MCB	Canada	Purchasing Manager
11	101116BEWO	Harrington's -- Calgary AB WOB	Canada	Purchasing Manager
12	101116BLAB	Harrington's -- Calgary AB ABB	Canada	Purchasing Manager
13	101116CATQ	Harrington's -- Calgary AB TQC	Canada	Purchasing Manager
14	101116CCTH	Harrington's -- Calgary AB THC	Canada	Purchasing Manager
15	101116CDMC	Harrington's -- Calgary AB MCC	Canada	Purchasing Manager
16	101116CEWO	Harrington's -- Calgary AB WOC	Canada	Purchasing Manager
17	101116CLAB	Harrington's -- Calgary AB ABC	Canada	Purchasing Manager
18	101116DATQ	Harrington's -- Calgary AB TQD	Canada	Purchasing Manager
19	101116DCTH	Harrington's -- Calgary AB THD	Canada	Purchasing Manager
20	101116DDMC	Harrington's -- Calgary AB MCD	Canada	Purchasing Manager


ShipTo Master Data

Count: 157

Descriptive Header Row Aids In Mapping

## Keep Data On Single Worksheet

The data for your import needs to be in the first worksheet of your import file. Only the first worksheet is considered by Master Data Import and all others are ignored.



AutoSave OFF Customer ShipTo Country & ShipTo Title 2020-10-15 - Saved

File Home Insert Page Layout Formulas Data Review View Help ACROBAT Share Comments

D618 Warehouse Supervisor


	A	B	C	D
1	Customer Ship-To	ShpTo Long Description	User Controlled ShipTo Country	User Controlled ShipTo Title
2	101116	Harrington's -- Calgary AB	Canada	Purchasing Manager
3	101116AATQ	Harrington's -- Calgary AB TQA	Canada	Purchasing Manager
4	101116ACTH	Harrington's -- Calgary AB THA	Canada	Purchasing Manager
5	101116ADMC	Harrington's -- Calgary AB MCA	Canada	Purchasing Manager
6	101116AEWO	Harrington's -- Calgary AB WOA	Canada	Purchasing Manager
7	101116ALAB	Harrington's -- Calgary AB ABA	Canada	Purchasing Manager
8	101116BATQ	Harrington's -- Calgary AB TQB	Canada	Purchasing Manager
9	101116BCTH	Harrington's -- Calgary AB THB	Canada	Purchasing Manager
10	101116BDMC	Harrington's -- Calgary AB MCB	Canada	Purchasing Manager
11	101116BEWO	Harrington's -- Calgary AB WOB	Canada	Purchasing Manager
12	101116BLAB	Harrington's -- Calgary AB ABB	Canada	Purchasing Manager
13	101116CATQ	Harrington's -- Calgary AB TQC	Canada	Purchasing Manager
14	101116CCTH	Harrington's -- Calgary AB THC	Canada	Purchasing Manager
15	101116CDMC	Harrington's -- Calgary AB MCC	Canada	Purchasing Manager
16	101116CEWO	Harrington's --	Canada	Purchasing Manager
17	101116CLAB	Harrington's --	Canada	Purchasing Manager
18	101116DATQ	Harrington's --	Canada	Purchasing Manager
19	101116DCTH	Harrington's --	Canada	Purchasing Manager
20	101116DDMC	Harrington's --	Canada	Purchasing Manager

ShipTo Master Data

Count: 157 100%

## Avoid Null Rows (They're Treated As The End of an Import)

Make sure you don't have a null row interspersed with rows of data in your import file. A Null row is a row without any data (note that a cell with all blank spaces or with zeroes in it is not considered null). The first null row that Master Data Import encounters in an import file will be treated as the end of your file. Master Data Import stops looking for data to import once it finds a null row. In this example, you'd want to remove row 14. If you don't, the import will stop at that row and not consider any of the rows of data after that point.



The screenshot shows an Excel spreadsheet with the following data:

	A	B	C	D
	Customer Ship-To	ShipTo Long Description	User Controlled ShipTo Country	User Controlled ShipTo Title
1		Harrington's -- Calgary AB	Canada	Purchasing Manager
2	101116	Harrington's -- Calgary AB TQA	Canada	Purchasing Manager
3	101116AATQ	Harrington's -- Calgary AB THA	Canada	Purchasing Manager
4	101116ACTH	Harrington's -- Calgary AB MCA	Canada	Purchasing Manager
5	101116ADMC	Harrington's -- Calgary AB WOA	Canada	Purchasing Manager
6	101116AEWO	Harrington's -- Calgary AB ABA	Canada	Purchasing Manager
7	101116ALAB	Harrington's -- Calgary AB TQB	Canada	Purchasing Manager
8	101116BATQ	Harrington's -- Calgary AB THB	Canada	Purchasing Manager
9	101116BCTH	Harrington's -- Calgary AB MCB	Canada	Purchasing Manager
10	101116BDMC	Harrington's -- Calgary AB WOB	Canada	Purchasing Manager
11	101116BEWO	Harrington's -- Calgary AB ABB	Canada	Purchasing Manager
12	101116BLAB	Harrington's -- Calgary AB TQC	Canada	Purchasing Manager
13	101116CATQ			
14				
15	101116CDMC	Harrington's -- Calgary AB MCC	Canada	Purchasing Manager
16	101116CEWO	Harrington's -- Calgary AB WOC		Purchasing Manager
17	101116CLAB	Harrington's -- Calgary AB ABC		Purchasing Manager
18	101116DATQ	Harrington's -- Calgary AB TQD		Purchasing Manager
19	101116DCTH	Harrington's -- Calgary AB THD		Purchasing Manager
20	101116DDMC	Harrington's -- Calgary AB MCD		Purchasing Manager

A callout box points to row 14, which is empty, and says "Eliminate Null Rows From Import File".

## Exclude Unnecessary Extras

Certain types of information should be excluded either because they don't make sense for an import, aren't necessary for an import, could disrupt the upload process\*, or could throw off the integrity of the import such as bring in unwanted data.


- **Exclude measure values, grand totals, and subtotals.** Only include dimension and master data in import files.
- **Delete any hidden rows from the Excel file**, otherwise they will show up in the data import preview and be included in the data that gets imported. If you don't want data from hidden rows, delete the rows from the Excel file before you import it.
- **Delete hidden columns from the Excel file**, otherwise they will show up in the data import preview. If you don't want data from hidden columns included in your import, delete the columns from the Excel file before you import it OR mark the columns as Ignore when mapping the data.
- In cases where you use an exported Stratum.Viewer view as the starting point when creating an import file, it is recommended that you disable or **exclude the following Viewer features before exporting the view.**
  - "All Others" rows or columns related to filtering.
  - Conditional format icons or formatting.
  - Charts.
  - Hyperlinks.
  - Calculated measure items that return images.
  - Pop-up labels on measure items.
  - Drilldown views linked up to rows, columns, or measure items.
- Also consider excluding specialty Excel items like the items listed below.
  - Images.

- Charts.
- Cell borders.
- Comments or notes.
- Excel features such as text boxes.

## Windows

### Attributes And Hierarchies Window

This window shows all attributes and hierarchies that exist for a dimension. The window is accessible when you are working with a User Controlled Attribute in the [User Controlled Attribute Maintenance window](#). The attributes and hierarchies for a dimension must have unique names. This window helps you plan out names for new attributes and hierarchies by seeing the names already used for the dimension's existing ones.





## Data Mapping – Master Data Import Window

### Data Mapping - Master Data Import

↻
←
?

1

Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option: Update

Validate
Configuration

4

Preview of rows 1 - 100

Dimension ▼

Attribute ▼

Attribute ▼

Attribute ▼

Ignore ▼

Ignore

Customer Priority ▼	User Controlled CPrty ... ▼	User Controlled CPrty ... ▼	- Select a Target - ▼		
<b>Customer Priority</b>	<b>CPrty Service Level</b>	<b>CPrty Contact Person</b>	<b>User Controlled CPrty Contact Email</b>	<b>es Sales Amount</b>	<b>Actual Sales</b>
A	Premium	Mary Leonard	User Controlled CPrty Contact Person	846	75,695,959
B	Professional	Phil Wilson	User Controlled CPrty Service Level	76	5,069,254
C	Standard	Karon Shype	kshype@companyabc.com	\$532,635,185	8,416,802
D	Standard 2	Karen Shype	kshype@companyabc.com	\$532,635,185	8,416,802
E	Professional 2	Phil Wilson	pwilson@companyabc.com	\$532,635,185	8,416,802
F	Premium Pro	Mary Leonard	mleonard@companyabc.com	\$532,635,185	8,416,802
G	Pro Admin	Gary Stevens	gstevens@companyabc.com	\$532,635,185	8,416,802
H	Standard Admin	Karen Shype	kshype@companyabc.com	\$532,635,185	8,416,802
I	Certified Partner	Ruth Garrette	rgarrette@companyabc.com	\$532,635,185	8,416,802

1	<b>Toolbar -</b> <ul style="list-style-type: none"> <li><b>Submit The Master Data Import For Processing</b>  - Click to process the Master Data Import. Once you confirm you want to proceed, the mapping window closes and you're returned to the <a href="#">Master Data Import list window</a>.</li> <li><b>Exit</b>  - Click to exit this window and return to the Master Data Import list window. Nothing will be saved or processed for the import you were setting up.</li> <li><b>Help</b>  - Click to open help that is specific to working with Master Data Imports.</li> </ul>
2	<b>Import Option</b> – Choose Update or Replace. An Update will update existing data and add any new data included in the import file. A Replace clears existing data for <b>all</b> of the User Controlled Attributes that belong to the import's Target dimension then adds data from the import file to the applicable attributes. Care should be taken when using a Replace since it removes data for <b>all</b> of a dimension's User Controlled Attributes even if the attributes aren't included in the import file. If there is existing data you don't want to lose, then set the import configuration to Update instead of Replace. See also <a href="#">When To Do An Update Vs. When To Do A Replace For Your Master Data Imports</a> .
3	<b>Data Mapping Preview</b> – This section shows up to a 100-row preview of your import file. The drop-down lists in the first two rows are for use in mapping import file data to Stratum – use them to tell Viewer what's in each column, what to do with the data during the import, and what columns if any to ignore. Row(s) highlighted in green are the start of you import file and what you indicated to Viewer were the header rows in the file (through a property in <a href="#">Import Configuration</a> ). <div style="border: 1px solid gray; padding: 5px; margin-top: 10px;"> <p><b>Note:</b> Header rows contain descriptive details that aid you in mapping but do not get imported. For example, the header rows contain dimension names, descriptions, and attribute names.</p> </div> <p>This example shows a progression of identifying what's in your import file using drop-down lists in the mapping window. As you do more imports in Viewer after your initial one, some mapping may be done</p>

for you automatically based on what Viewer has learned about your prior import habits. You can change automatic selections if needed.

Here is the initial state of the import preview. Viewer was able to map the first column to a dimension through automatic mapping. That column mapped to the Type of Dimension and a Target dimension of Customer Priority. All other columns defaulted to Ignore. Also, Master Data Import assumed that the import file had one header row, which is the row displayed with a green background.

### Data Mapping - Master Data Import

Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option: Update ▼ Validate Configuration Preview of rows 1 - 100

Dimension ▼	Ignore ▼	Ignore ▼	Ignore ▼
Customer Priority ▼			
<b>Customer Priority</b>	<b>CPrty Service Level</b>	<b>CPrty Contact Person</b>	<b>Cprty Contact Email</b>
A	Premium	Mary Leonard	mleonard@companyabc.com
B	Professional	Phil Wilson	pwilson@companyabc.com
C	Standard	Karen Shype	kshype@companyabc.com
D	Standard 2	Karen Shype	kshype@companyabc.com
E	Professional 2	Phil Wilson	pwilson@companyabc.com
F	Premium Pro	Mary Leonard	mleonard@companyabc.com
G	Pro Admin	Gary Stevens	gstevens@companyabc.com
H	Standard Admin	Karen Shype	kshype@companyabc.com
I	Certified Partner	Ruth Garrette	rgarrette@companyabc.com

Drop-down lists for the next three columns were used to identify each of them as attributes. They have the values to be import for the dimension. For each column, Attribute was chosen for the type then the Target drop-down lists for each column were used to choose the User Controlled Attributes to receive the imported data. These types of attributes must be set up in advance of the import using Viewer's User Controlled Attribute Maintenance functionality.

### Data Mapping - Master Data Import

Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option: Update ▼ Validate Configuration Preview of rows 1 - 100

Dimension ▼	Attribute ▼	Attribute ▼	Attribute ▼
Customer Priority ▼	User Controlled CPrty Serv...	User Controlled CPrty Cont...	
<b>Customer Priority</b>	<b>CPrty Service Level</b>	<b>CPrty Contact Person</b>	
A	Premium	Mary Leonard	
B	Professional	Phil Wilson	pwilson@companyabc.com
C	Standard	Karen Shype	kshype@companyabc.com
D	Standard 2	Karen Shype	kshype@companyabc.com
E	Professional 2	Phil Wilson	pwilson@companyabc.com
F	Premium Pro	Mary Leonard	mleonard@companyabc.com
G	Pro Admin	Gary Stevens	gstevens@companyabc.com
H	Standard Admin	Karen Shype	kshype@companyabc.com
I	Certified Partner	Ruth Garrette	rgarrette@companyabc.com

Here's the Target attribute being selected for the last attribute column in the preview. The mapping is complete, and the user can process the import.

## Data Mapping - Master Data Import



Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option: Update ▼

Validate

Configuration

Preview of rows 1 - 100

Dimension ▼	Attribute ▼	Attribute ▼	Attribute ▼
Customer Priority ▼	User Controlled CPrty Serv... ▼	User Controlled CPrty Cont... ▼	- Select a Target - ▼
<b>Customer Priority</b>	<b>CPrty Service Level</b>	<b>CPrty Contact Person</b>	<b>User Controlled CPrty Contact Email</b>
A	Premium	Mary Leonard	User Controlled CPrty Contact Person
B	Professional	Phil Wilson	User Controlled CPrty Service Level
C	Standard	Karen Shype	kshype@companyabc.com
D	Standard 2	Karen Shype	kshype@companyabc.com
E	Professional 2	Phil Wilson	pwilson@companyabc.com
F	Premium Pro	Mary Leonard	mleonard@companyabc.com
G	Pro Admin	Gary Stevens	gstevens@companyabc.com
H	Standard Admin	Karen Shype	kshype@companyabc.com
I	Certified Partner	Ruth Garrette	rgarrette@companyabc.com

4

**Validate** – Click anytime while mapping your data to validate the mapping. If Viewer encounters something like a row that's missing key values for the Target dimension or mapping selections that are required but haven't been made yet, it will present a message about those issues.

**Configuration** – Click to access the [Import Configuration window](#). From there, you can edit basic properties that tell Viewer how to treat the import file, the Target dimension, and how many header rows are in the import file.

## Import Configuration Window For Master Data Imports

<p>1</p>	<p><b>General –</b></p> <ul style="list-style-type: none"> <li>• <b>Import Option</b> - Choose Update or Replace. <ul style="list-style-type: none"> <li>• An Update will update existing data and add any new data included in the import file.</li> <li>• A Replace clears existing data for <b>all</b> of the User Controlled Attributes that belong to the import's Target dimension then adds data from the import file to the applicable attributes. Care should be taken when using a Replace since it removes data for <b>all</b> of a dimension's User Controlled Attributes even if the attributes aren't included in the import file. If there is existing data you don't want to lose, then set the import configuration to Update instead of Replace. See also <a href="#">When To Do An Update Vs. When To Do A Replace For Your Master Data Imports</a>.</li> </ul> </li> <li>• <b>Target Dimension</b> - The Target dimension is the one with the attribute(s) that will receive imported data. User Controlled Attributes from that dimension will be available to select when you map imported data to Stratum.</li> </ul> <hr/> <p><b>Note:</b> Once you have done a few imports, Master Data Import learns about your import data habits and can do some automatic configuration and Data Mapping. When that happens, the Import Configuration window is bypassed. You can open it anytime by clicking the Configuration button in the Data Mapping window.</p>
<p>2</p>	<p><b>File Data –</b> Make selections about how your file is set up. Use <b>Header Rows In File</b> to specify how many header rows are in the import file. Header rows contain descriptive details that aid you in mapping but do not get imported. For example, the row(s) contain dimension names, descriptions, or attribute names.</p>





Master Data Import List Window

Master Data Import

1



2

File Name ▲	Dimension	Owner	Submitted	Completed	Status
KEF For Customer Priority Service Level replace.xlsx	Customer Priority	Karen Shype	09/10/2020 17:43:38	09/10/2020 17:43:56	Completed
Product - Seeding User Controlled with Corp Controlled.xlsx	Product	Karen Shype	09/11/2020 13:36:45	09/11/2020 13:37:13	Completed
UPC Global Number Data For Marketing Promotion Code.xlsx	UPC Global Number	Karen Shype	09/11/2020 13:42:52	09/11/2020 13:43:11	Completed
UPC Global Number Seasonal Spend Data.xlsx	UPC Global Number	Karen Shype	09/11/2020 13:43:18		In Process
1 to 4 of 4    ⏪ ⏩ ⏴ ⏵					

1	<p><b>Toolbar –</b></p> <ul style="list-style-type: none"><li><b>New</b>  - Click to set up a new Master Data Import, which will import data into <a href="#">User Controlled Attributes</a>.</li><li><b>See Processing Details For A Master Data Import</b>  - Select an import and then click this button to see a summary of all properties for the import. See also <a href="#">Review Processing Details For A Master Data Import</a>.</li><li><b>Delete</b>  - Select an import and then click the Delete button to delete its applicable records such as its processing report details and upload file. The imported data is not impacted by the delete.</li><li><b>Help</b>  - Click to open help that is specific to working with Master Data Imports.</li></ul>
2	<p><b>Master Data Imports and Status Information –</b> The list window shows all Master Data Imports that users have created and submitted for processing. Details include the name of the import file, dimension involved in the import, when imports were submitted and when their processing was completed. The status for a Master Data Import will be In Process, Completed, or Error.</p>

## System Configuration Window

### Customer Info & Keys Section



1

### System Configuration

#### Customer Info and Keys

2

Name:

Global Home Page:

Registration Keys: Stratum.Viewer

3

Stratum Access Hub



Stratum Analyst Hub

Stratum Cloud Import

Customer Number:

4

Customer Type: Hosted

1	<b>Toolbar -</b> <ul style="list-style-type: none"><li><b>Save</b>  - Click to save changes to system configuration.</li><li><b>Help</b>  - Click to open help that is specific to working with system configuration.</li></ul>
2	<b>Name</b> - Use this field to customize the name that displays for the application in the browser title bar and tab. <b>Global Home Page</b> - Use this field to define a custom, global home page for Stratum.Viewer. The home page can open to a web site, document, directory, or other supplementary information that would be meaningful for users. If you leave this field blank, the application home page defaults to a Stratum home page that has links to Stratum.Viewer videos and other resources. If needed, administrators can define different home pages for particular users or user groups through settings in the User Profile or User Profile Group windows.
3	<b>Registration Keys</b> - A valid registration key is required for licensed copies of Stratum and specialized functionality within it. If you receive a message about a missing or invalid key, contact Silvion Support at (800) 474-5866 or <a href="mailto:CustomerSupport@silvon.com">CustomerSupport@silvon.com</a> . License keys are required for: <ul style="list-style-type: none"><li>Stratum.Viewer</li><li>Stratum Access Hub, which includes the Stratum Broadcast Manager plus Excel exporting and Stratum Power BI Connector functionality.</li><li>Stratum Analyst Hub, which includes Planning, Data Import, and Master Data Import features.</li></ul>

	<ul style="list-style-type: none"><li>Stratum Cloud Import, which extends Data Import functionality to allow for Data Steward functionality and to import local SQL Server databases or Azure cloud sources.</li></ul>
4	<p><b>Customer Number</b> - This is a unique identification number for your Stratum.Viewer implementation. Contact Silvon Support at (800) 474-5866 or <a href="mailto:CustomerSupport@silvon.com">CustomerSupport@silvon.com</a> if you do not have a valid customer number.</p> <p><b>Customer Type</b> – This is a read-only property. It tells you if the environment is Hosted or On-Premise.</p>

**System Generated Emails Section**

System Generated Emails

1

SMTP Server:

2

Email From Address:

No-Reply@silvoncloud.com

3

Broadcast Server:

Distributed Email Subject Prefix When No Data Exists

\*\*No Data Exists\*\*

Process Completed Email

Address:

Subject:

Process Completed for Stratum Broadcast Schedule / Broadcast Group / Action

Body:

See the attached log for information on the Stratum Broadcast Schedule / Broadcast Group / Action process.

☒ Attach Process Log

Process Failed Email

Address:

Subject:

Process Failed for Stratum Broadcast Schedule / Broadcast Group / Action

Body:

See the attached log for information on the Stratum Broadcast Schedule / Broadcast Group / Action process.

☒ Attach Process Log

4

Data Imports: Process Completed Email

Address:

Subject:

Process Completed for Data Import

Body:

See the attached log for information on the Data Import process.

☐ Attach Process Log

Process Failed Email

Address:

Subject:

Process Failed for Data Import

Body:

See the attached log for information on the Data Import process.

☒ Attach Process Log

1	<p><b>SMTP Server</b> - This setting controls how Stratum.Viewer delivers the emails that it generates. The property defaults to a "localhost" value, in which case Stratum.Viewer emails will be delivered using the SMTP configurations for the server where Stratum.Viewer resides.</p>
---	--

Copyright 2024 Silvon Software, Inc. *All rights reserved. (Last Revised: October 2024)*

29



	<p>If you plan to use an SMTP server other than the default for delivering Stratum.Viewer generated emails, enter that server name in the SMTP Server field. Enter the server name in a format that will be recognized by your network. For example, the server name or IP address or in the format of server name.network name.com.</p> <hr/> <p><b>Note:</b> If you are not sure which default SMTP server is used for the Stratum.Viewer server, access Microsoft Internet Information Services Manager on the server and look at the Default SMTP Virtual Server settings.</p>
<p>2</p>	<p><b>Email From Address</b> – This property is used by administrators to specify the email address that will show as the sender of Data Import processing notification emails.</p> <ul style="list-style-type: none"> <li>• An address must be specified if you want Data Import processing emails to be sent.</li> <li>• If your environment is a hosted environment, you should use <a href="mailto:No-Reply@silvoncloud.com">No-Reply@silvoncloud.com</a> as the Email From Address.</li> </ul> <hr/> <p><b>Note:</b> Processing emails for Actions, Broadcast Groups, and Broadcast Schedules will still be sent even if you don't specify this Email From Address – for those items, the “From” email is the email of the Stratum user who interactively processed the Action, Broadcast Group, or Broadcast Schedule from Viewer. When those items are scheduled to be processed in batch, the “Email From Address” in System Configuration is the sender of the email by default. If an address isn't specified, the scheduled process will use the email address of the account used to run the batch job or you can specify an email using an optional “FromEmailAddress” parameter specific to batch jobs. More details are in the section of help dedicated to Actions, Broadcast Group, and Broadcast Schedule topics.</p>
<p>3</p>	<p><b>Broadcast Server email properties</b> are described below. These are sent when actions, broadcast groups, and broadcast schedules are processed from Stratum.Viewer. Typical recipients you might specify are Broadcast Manager administrators or other interest parties who need to know what's happening with the Broadcast Manager.</p> <p><b>Distributed Email Subject Prefix When No Data Exists</b> – This text controls the default subject prefix for emails of actions that would generate blank results – an action where no data is available to generate a report. Those cases occur when an Email action would result in no data to send to the designated user or a File action would result in no data in the resulting shared file. For example, if there are no rows and columns returned for a view that tracks excessive returns because no rows satisfy filter criteria of YTD Return Amount greater than \$40,000.</p> <p>The prefix is only used when an action's “Send Email when no Data Exists” property has been set to Yes and when no data exists. The prefix defined here will be used in the action email subject line before the rest of the Subject field text unless the user customized the prefix text for their specific action.</p> <hr/> <p><b>Note:</b> If a user sets an action's “Send Email when no Data Exists” property to No and a no data case occurs, then no email will be generated by the action.</p> <hr/> <p><b>Process Completed Email / Process Failed Email</b> – The properties in these two sections are used to automatically send emails to the designated recipients that tell them about the processing of Broadcast Schedules, Broadcast Groups, and Actions. Process Completed emails indicate a process completed. Process Failed emails indicate a process failed. The emails give greater visibility into what's happening with the Stratum Access Hub's Broadcast Manager.</p> <p>For each type of email, specify the email addresses, subject, and body text for the messages. Use a semicolon or comma to separate email addresses if you specify more than one recipient.</p> <p>Processing logs can be attached to these emails to provide more detailed information about a process.</p>

4	<p><b>Data Import email properties</b> are described below. These are sent when data imports are processed from Stratum.Viewer as long as you also have specified an Email From Address in the System Configuration window. Typical recipients you might specify are administrators, Data Stewards or other interested parties who need regular visibility into what’s happening with the Stratum Analyst Hub’s Data Import.</p> <p><b>Process Completed Email / Process Failed Email</b> – The properties in these two sections are used to automatically send emails to the designated recipients that tell them about the processing of Data Imports. Process Completed emails indicate a process completed. Process Failed emails indicate a process failed. The emails give greater visibility into what’s happening with Data Imports.</p> <p>For each type of email, specify the email addresses, subject, and body text for the messages. Use a semicolon or comma to separate email addresses if you specify more than one recipient.</p> <p>Processing logs can be attached to these emails to provide more detailed information about a process. For hosted environments, Silvion has validations in place to prevent processing logs from being attached to system-generated emails if a recipient’s email isn’t associated with Silvion’s hosted domain for Stratum Cloud. This protects sensitive information from being shared with non-administrators or outside email addresses. For example, logs would only be sent to emails from @silvoncloud.com or @silvon.com.</p>
---	--

## Process Options Section

**Process Options**

1

Broadcast Server: ☐ Override Log File Location For Broadcast Process (specify new location below)

2

Data Imports: Master Data Import Upload File Location
Data Import Upload File Location

1	<p><b>Override Log File Location For Broadcast Process</b> – This <b>Broadcast Server</b> property can be used to customize where log files from Broadcast Server processing are stored. The logs are from the processing of broadcast schedules, broadcast groups, and actions. By default, logs are stored in the ‘\Logs\Broadcast Server’ sub-folder in the directory where your Stratum.Viewer implementation is installed. If you want to change the log file location, select the Override Log File Location checkbox and enter the location in the related field. The location you specify must exist already and be one to which your company’s Action Processing Account has access rights.</p>
2	<p><b>Upload File Locations</b> – The properties in the <b>Data Imports section</b> are applicable when Master Data Import or Data Import functionality are used with your implementation. These locations are used by Data Import and Master Data Import.</p> <ul style="list-style-type: none"> <li>When specifying a location, use the full UNC path format \\host-name\share-name\file_path\ and include a backslash mark \ as the final character. For example: \\serverabc\User Controlled Data\Uploaded Import Files\</li> <li>The Master Data Import location is used when importing values into User Controlled Attributes.</li> <li>The Data Import location is used when importing values into User Controlled Measures. To support Data Imports where CSV or Text files are the data source, the Data Import Upload File Location should be on the same server as where the Stratum.Server database resides.</li> </ul> <p>The locations must be ones that exist already and ones for which your implementation’s Viewer Impersonation account has access rights (read and write access). See account access requirements defined in the Master Data Import and Data Import sections of help.</p>

Cloud Import Locations Section

Cloud Import Locations

Azure Blob Container: Folder Name

Signature

1

Azure File Share: Folder Name

Signature

Azure SQL Database: Connection String

Local SQL Server Database: Connection String

2

1	<p>Data Imports using data from Azure cloud sources is only allowed if your environment is licensed for Stratum Cloud Import. Use the applicable fields provided in this section of System Configuration for supplying connection details about Azure sources for your imports.</p> <ul style="list-style-type: none"><li><b>Azure Blob Container</b> – enter Folder Name and Signature details.</li><li><b>Azure File Share</b> – enter Folder Name and Signature details.</li><li><b>Azure SQL Database</b> – Enter the Connection String.</li></ul> <hr/> <p><b>*Note:</b> Existing knowledge and experience with Azure is required when setting up Stratum to do imports from Azure cloud sources. Use your knowledge of your Azure implementation to determine the appropriate URL, connection string, and folder details to copy from Azure into the connection detail fields in System Configuration.</p>
2	<p>Data Imports using data from local SQL Server databases are only allowed if your environment is licensed for Stratum Cloud Import. Use the applicable field provided in this section of System Configuration for supplying connection details about that type of source for your imports.</p> <p><b>Local SQL Server Database</b> – Enter the Connection String.</p>

Microsoft Analysis Services Section

Microsoft Analysis Services

Connection Pool Properties: Idle Connection Time Limit

1

600

Maximum Connections Per Role

5

Connection Time Limit:

600


1

**Connection Pool Properties** - Connection pools for Stratum.Viewer are managed via Stratum.Viewer rather than via Microsoft Analysis Services. To support this connection pooling, two parameters are available. The settings determine how many connection pool connections can exist for each user's role and how long idle connections can be left open before Stratum.Viewer closes them.

- Idle Connection Time Limit** - The value for this parameter determines how many seconds a connection can remain idle before its times out and is removed from the connection pool. The default and recommended value is 600. In most cases, this setting allows for an optimal balance between the performance time of connecting to retrieve data from the Stratum.Connector Analysis Services database and the resources required on the Stratum.Viewer server to maintain the connection pool.
- Maximum Connections Per Role** - The value for this parameter determines how many open connections will be maintained in the connection pool for each user's role. The default and recommended value is 5. That means that a maximum of five open data connections will be maintained in the pool for each user's role. In most cases, this setting allows for an optimal balance between the performance time of connecting to retrieve data from the Stratum.Connector Analysis Services database and the resources required on the Stratum.Viewer server to maintain the connection pool.

**Connection Time Limit** – This setting should **not** be changed unless you are directed to by Silvion Support. The setting impacts how long parts of processes handled by Stratum.Connector are given to complete those parts before the process times out.

## User Controlled Attribute List Window



1

**Toolbar -**

- New** - Click to set up a new User Controlled Attribute.\*
- Edit** - Select the attribute you want to edit and then click the Edit button.\*
- See A History Of Changes For This Attribute** - Select an attribute then click this button to see a summary of its properties when it was first added and any changes made to its properties since that time. See also [Review History Of Changes For User Controlled Attribute](#).

**Note:** If you click the history button on the list window without first selecting an attribute, a history file opens for all User Controlled Attributes including any previously deleted attributes.

- Delete** - Select the attribute to delete and then click the Delete button. Deleting the attribute means the attribute and any data you imported for it will be removed and no longer available in Stratum.Viewer.\*
- Help** - Click to open help that is specific to working with User Controlled Attributes.


**\*Note:** Your additions, edits, and deletions done for User Controlled Attributes will be reflected in Stratum.Viewer after the next Full process occurs in Stratum.Connector.

2

**Current List –** Use this drop-down list to filter the list window. Choose a specific dimension to see only the User Controlled Attributes that exist, if any, for that dimension. Or leave the list set to All Dimensions to see all User Controlled Attributes for all dimensions.

	<p><b>Search</b> – Search by attribute name. Type in your text and then click the search icon or press the Enter key on your keyboard.</p>
3	<p><b>Attributes, Pending Status, and Other Status Information</b> – The list window provides a number of details about a User Controlled Attribute including its dimension, name, when it was created or last updated, if it has pending changes for it, and details of any master data imports done for the attribute.</p> <ul style="list-style-type: none"><li>• <b>Pending Updates</b> – Indicates whether there are pending changes for the attribute that are not yet available in Viewer. “Yes” means there are pending changes. The attribute’s current state as shown here may not match what is in Viewer. “No” means there are no pending attribute updates. The attribute’s current state as shown here matches what is in Stratum.Viewer. If Pending Updates = “Yes”, then a Full process in Stratum.Connector is required. Contact your Stratum administrator for information about when the next Full process is scheduled.</li><li>• <b>Last Import / Last Imported By</b> – Shows the last date of any master data import done for the attribute and who did the import.</li></ul>

## User Controlled Attribute Maintenance Window



**User Controlled Attribute Maintenance**

**General**

Dimension: Customer Parent

Attribute: User Controlled CPnt Emails

Default Value: ?

Create Hierarchy: Yes

Hierarchy Name: Customer Parent User Controlled CPnt Emails

Level Name: Customer Parent User Controlled CPnt Emails

**Details**







Last Updated Date: 7/14/2020 4:36:13 PM

Last Updated By: Karen Farrelly

Pending Updates: No

Last Master Data Import Date: 7/8/2020 4:05:54 PM

Last Master Data Import By: Karen Farrelly



<p>1</p>	<p><b>Toolbar -</b></p> <ul style="list-style-type: none"> <li>• <b>Save</b>  - Click to save the new or edited attribute.*</li> <li>• <b>See A History Of Changes For This Attribute</b>  - Select an attribute then click this button to see a summary of its properties when it was first added and any changes made to its properties since that time. See also <a href="#">Review History Of Changes For User Controlled Attribute</a>.</li> <li>• <b>See All The Attributes For The Selected Dimension</b>  - Click to see a full list of <a href="#">Corporate</a> and <a href="#">User Controlled</a> Attributes for the dimension related to the attribute with which you are currently working. See also <a href="#">Attributes And Hierarchies Window</a>.</li> <li>• <b>Delete</b>  - Click to delete the attribute. Deleting the attribute means the attribute and any data you imported for it will be removed and no longer available in Stratum.Viewer.*</li> <li>• <b>Exit</b>  - Click to exit this window and return to the <a href="#">User Controlled Attribute list window</a>.</li> <li>• <b>Help</b>  - Click to open help that is specific to working with User Controlled Attributes.</li> </ul> <p><b>*Note:</b> Your additions, edits, and deletions done for User Controlled Attributes will not be reflected in Stratum.Viewer until <b>after</b> the next Full process occurs in Stratum.Connector.</p>
<p>2</p>	<p><b>General</b> – Control all the properties for the User Controlled Attribute from this section. Also use the section to optionally add a hierarchy based on the attribute.</p> <ul style="list-style-type: none"> <li>• <b>Dimension</b> - Choose the dimension to which you want the attribute added.</li> <li>• <b>Attribute</b> - Enter a name for the attribute.</li> </ul>




	<ul style="list-style-type: none"> <li>• <b>Default Value</b> - Specify a character(s) to display as the default value for the attribute. That value will be used for key values that do not yet have data for the attribute. When you see the default value for an attribute in a view, that indicates data does not currently exist for the attribute. For example, if you have not imported data for the attribute using Master Data Import functionality, all key values will be set to the default value. This property defaults to “?” but you can customize it to any text you prefer to use, up to 50 characters.</li> <li>• <b>Create Hierarchy?</b> - Optionally create a hierarchy based on the new attribute. Creating a hierarchy for it lets you see your data summarized by that attribute by making the attribute available as a level that can be included in rows / columns of a view. “Yes” will create it and enable the name fields below it. You can customize the name of the hierarchy and the level that gets created for it. Names must be different than the attribute on which they are based. The hierarchy and level name default to the name of the dimension for the attribute followed by the name given to the attribute. “No” will skip creating the hierarchy.</li> </ul>
3	<p><b>Attribute Details</b> – This section tells you when the attribute was created or last updated, and the person who made the changes. Other details tell you if there are pending changes for the attribute and show details of the most recent master data import done for the attribute.</p> <ul style="list-style-type: none"> <li>• <b>Pending Updates</b> – Indicates whether there are pending changes for the attribute that are not yet available in Viewer. “Yes” means there are pending changes. The attribute’s current state as shown here may not match what is in Viewer. “No” means there are no pending attribute updates. The attribute’s current state as shown here matches what is in Stratum.Viewer. If Pending Updates = “Yes”, then a Full process in Stratum.Connector is required. Contact your Stratum administrator for information about when the next Full process is scheduled.</li> <li>• <b>Last Master Data Import Date / By</b> – Shows the last date of any master data import done for the attribute and who did the import.</li> </ul>


## Advanced Concepts

### Edit Names Of User Controlled Attributes


1. Click Manage Things then User Controlled Attributes from the main menu in the top panel of Stratum.
2. In the [User Controlled Attribute list window](#), double-click the name of the applicable attribute or click it then click Edit .
3. Edit the name using the Attribute property in the [User Controlled Attribute Maintenance window](#).
4. Save  the change. You are returned to the list window where the change shows with a Pending Updates status of Yes. The name change will be reflected in Stratum.Viewer once pending updates are processed. That happens **after** the next Full process occurs in Stratum.Connector. Contact your Stratum administrator for information about when the next Full process is scheduled.

### Edit Names Of Hierarchies And Levels Based On User Controlled Attributes



1. Click Manage Things then User Controlled Attributes from the main menu in the top panel of Stratum.
2. In the [User Controlled Attribute list window](#), double-click the name of the attribute for the hierarchy or level. You can also click it then click Edit .

3. Edit the name of the hierarchy and/or level using their Name properties in the [User Controlled Attribute Maintenance window](#).
4. Save  the changes. You are returned to the list window where the change shows with a Pending Updates status of Yes. The name change will be reflected in Stratum.Viewer once pending updates are processed. That happens **after** the next Full process occurs in Stratum.Connector. Contact your Stratum administrator for information about when the next Full process is scheduled.

## Remove User Controlled Attributes


1. Click Manage Things then User Controlled Attributes from the main menu in the top panel of Stratum.
2. In the [User Controlled Attribute list window](#), click the name of the attribute.
3. Click Delete .
4. Click OK in the prompt that displays to proceed with the deletion. The deletion will take place after the next Full process occurs in Stratum.Connector. It will remove the User Controlled Attribute, any key values created for it, and any master data previously imported for it.

## Remove Hierarchies Based On User Controlled Attributes


1. Click Manage Things then User Controlled Attributes from the main menu in the top panel of Stratum.
2. In the [User Controlled Attribute list window](#), double-click the name of the attribute for the hierarchy. You can also click it then click Edit .
3. Change the Create Hierarchy property to No in the [User Controlled Attribute Maintenance window](#).
4. Save  the changes. You are returned to the list window where the change shows with a Pending Updates status of Yes. The hierarchy and its level will be removed from Stratum.Viewer once pending updates are processed. That happens **after** the next Full process occurs in Stratum.Connector. The hierarchy and level will no longer be available to add to views, and they will be removed from views in which they were previously used. Contact your Stratum administrator for information about when the next Full process is scheduled.

## Review History Of Changes For User Controlled Attribute

The history file for a User Controlled Attribute captures information about when it was added, changed, or deleted. The file includes the date and time of the change, user details identifying who did the change, the dimension the attribute belongs to, and all related properties captured about the change from the [User Controlled Attribute Maintenance window](#). To see a history file, follow these steps.


1. If you already have the attribute open in the maintenance window, click See A History Of Changes For This Attribute .

OR

1. Click Manage Things then User Controlled Attributes from the main menu in the top panel of Stratum.
2. In the [User Controlled Attribute list window](#), select the applicable attribute then click See A History Of Changes For This Attribute .

**Note:** If you click the history button on the list window without first selecting an attribute, a history file opens for all User Controlled Attributes including any previously deleted attributes.


Here's a portion of a history file showing a recent change impacting an attribute for the Customer Ship-To dimension. The Update Type tells you the attribute was changed. The Property, Old Value, and New Value columns indicate what property changed and what the property was set to before and after the change. This change was an edit to the name of the attribute and to the names of the hierarchy and level based on that attribute. A newly added attribute doesn't have any information listed in the Old Value column, as you can see in the "Add" rows that are in the file.




	F	G	H	I	J	K
	Update Type	Attribute ID	Attribute Name	Attribute Dimension	Property	New Value
2	Change	1253	User Controlled ShipTo Title	Customer Ship-To	Attribute Name	ShipTo Title
3	Change	1253	User Controlled ShipTo Title	Customer Ship-To	Hierarchy	Customer ShipTo User Controlled ShipTo Title
4	Change	1253	User Controlled ShipTo Title	Customer Ship-To	Level	Customer ShipTo User Controlled ShipTo Title
5	Add	1253	ShipTo Title	Customer Ship-To	Attribute Name	ShipTo Title
6	Add	1253	ShipTo Title	Customer Ship-To	Dimension	Customer Ship-To
7	Add	1253	ShipTo Title	Customer Ship-To	Default Value	?
8	Add	1253	ShipTo Title	Customer Ship-To	Create Hierarchy	Yes
9	Add	1253	ShipTo Title	Customer Ship-To	Hierarchy	Customer Ship-To ShipTo Title
10	Add	1253	ShipTo Title	Customer Ship-To	Level	Customer Ship-To ShipTo Title
11						
12						
13						
14						
15						
16						
17						
18						
19						
20						
21						
22						
23						

## Review Processing Details For A Master Data Import

The Processing report provides detailed summaries of a Master Data Import. The report is an Excel file containing all details about an import, such as the [Target dimension](#) for the import and the User Controlled Attributes to which data was imported. The report also indicates the status of the different stages of processing for an import. To open a report:

1. Click Analyst Tools then Master Data Import from the main menu in the top panel of Stratum.
2. In the [Master Data Import list window](#), select the applicable import then click See Processing Details For A Master Data Import .

Here's an example report. The start of it shows general details like the name of the import file, who created and submitted the import for processing, and when processing was completed. Next are Import Configuration details that show selections made in that window. The next section, which contains Processing Details, show the names of database tables involved in the import then the names and status details for each processing stage.



Master Data Import Processing Details:	
Import File Name:	KEF For UPC Global Number.xlsx
Uploaded File Name:	KEF For UPC Global Numberaf08203064284ac2933f48e6caf4960f.xlsx
Data Import Status:	Completed
Owner:	Karen
Submitted:	07/10/2020 11:16:08
Completed:	07/10/2020 11:16:22
Import Configuration:	
Import Option:	Update
Target Dimension:	UPC Global Number
Header Rows In File:	1
Processing Details:	
Master File	dimension32group1mast8_48
Previous Transaction	
Source Transaction	dimension32group1mast0_48
Stage:	Save User Mapping
Process Status:	Completed
Start Date:	07/10/2020 11:16:08
Completed Date:	07/10/2020 11:16:08
Stage:	Common Area To Mast Table
Process Status:	Completed

Here are examples of the other two main sections of the file, The Data Mapping section shows each column in your import file and how it was mapped to Stratum items in the [Data Mapping window](#). The Target dimension and User Controlled Attributes for the import are listed there. The total number of rows that were imported displays in the Number of Rows section at the end of the file.

	A	B
29	Completed Date:	07/10/2020 11:16:09
30		
31	Stage:	<b>Mast Table To Dimension</b>
32	Process Status:	Completed
33		Transaction Table Created: dimension32group1mast8_48
34	Start Date:	07/10/2020 11:16:09
35	Completed Date:	07/10/2020 11:16:22
36		
37	Stage:	<b>Post Process</b>
38	Process Status:	Completed
39	Start Date:	07/10/2020 11:16:22
40	Completed Date:	07/10/2020 11:16:22
41		
42	<b>Data Mapping:</b>	
43	<b>Column A</b>	
44	Type	Dimension
45	Target	UPC Global Number
46	<b>Column C</b>	
47	Type	Attribute
48	Target	KEF Revised UPC Market Promotion Code edit
49	<b>Column D</b>	
50	Type	Attribute
51	Target	KEF Revised UPC Lead Time in Days Yes Hierarchy
52		
53	<b>Number of Rows</b>	84
54		
55		

## Understanding Your Imported Master Data

The following information helps you understand what data will display in views for the User Controlled Attributes that you create and for any hierarchies created from those attributes.

- Default Values Show For User Controlled Attributes Until You Import Master Data** –The default value assigned to a User Controlled Attribute at the time you created it will display for all of its members that do not yet have master data. As you begin importing master data for them, the default value members will be replaced with your imported data. In the following example, the User Controlled CPnt Shipping Status attribute has had master data imported for some but not all of its members. The default value assigned to the attribute was a question mark ?. The five members displaying that mark are ones for which master data has not been imported yet.

★ Weekly ShipTo Numbers

View Filter: Customer Sold-To: Multiple

Customer Parent	CPnt Long Description	User Controlled CPnt Shipping Status	▼ Sales Wk 1 to Wk 38 2020	Sales Wk 1 to Wk 38 2019
<a href="#">5000</a>	Wilder Foods	Same Day Shipping Available	\$2,295,577,068	<a href="#">\$2,176,513,036</a>
<a href="#">5002</a>	Harrington's	Ship Time > 3 days	\$1,005,788,020	<a href="#">\$940,793,462</a>
<a href="#">5003</a>	Good Foods, Inc.	Back Order	\$827,582,591	<a href="#">\$787,879,083</a>
<a href="#">5001</a>	Sumpter Distribution	Special Order, Shipping Times Vary	\$629,707,288	<a href="#">\$586,746,498</a>
<a href="#">6007</a>	Oliveri	Back Order	\$264,721,709	<a href="#">\$248,510,128</a>
<a href="#">6006</a>	Penn Brands	Ship Time > 3 days	\$176,990,405	<a href="#">\$169,913,204</a>
<a href="#">6009</a>	Prestwick Inc	Same Day Shipping Available	\$150,217,528	<a href="#">\$143,075,609</a>
<a href="#">6005</a>	Midwest Providers	Ship Time > 3 days	\$145,992,033	<a href="#">\$136,049,687</a>
<a href="#">6016</a>	Southwest Inc	Back Order	\$104,492,865	<a href="#">\$98,341,945</a>
<a href="#">6014</a>	Chicagos Finest	?	\$98,318,253	<a href="#">\$93,307,683</a>
<a href="#">6051</a>	Quebec Foods	Ship Time > 3 days	\$89,506,744	<a href="#">\$82,047,038</a>
<a href="#">6052</a>	Canadian Imports Inc	Ship Time > 3 days	\$81,256,185	<a href="#">\$73,804,632</a>
<a href="#">6011</a>	NY Foods	?	\$79,952,777	<a href="#">\$70,900,984</a>
<a href="#">6017</a>	Packingham Corp	Ship Time < 3 days	\$76,716,283	<a href="#">\$70,775,833</a>
<a href="#">6015</a>	St Louis Dist Inc	Same Day Shipping Available	\$74,263,077	<a href="#">\$71,221,327</a>
<a href="#">6008</a>	Dallas Food Service	Back Order	\$73,591,830	<a href="#">\$67,855,885</a>
<a href="#">6053</a>	Alberta Foods	Ship Time > 3 days	\$72,279,662	<a href="#">\$69,443,385</a>
<a href="#">6010</a>	Smith Inc	?	\$71,228,702	<a href="#">\$67,441,839</a>
<a href="#">6050</a>	Maple Tree	Special Order, Shipping Times Vary	\$68,034,480	<a href="#">\$62,095,408</a>
<a href="#">6013</a>	Auburn Providers	?	\$63,568,723	<a href="#">\$56,429,091</a>
<a href="#">6012</a>	Montelissi	?	\$60,767,003	<a href="#">\$54,404,904</a>

- Imported Values Are Used As Hierarchy Members For Hierarchies Created From User Controlled Attributes** – You have the option to create a hierarchy from an User Controlled Attribute. This lets you see your data summarized by that attribute by making the attribute available as a level that can be included in rows / columns of a view. The master data you import for a User Controlled Attribute also is used to populate the members of its hierarchy/level if you opted to create a hierarchy from that attribute. In this example, the first level on rows is from a hierarchy that was created from a User Controlled Attribute. The values a user imported for the attribute are what became the members for that hierarchy's level.

The Shipping Status attribute in the prior example had a hierarchy created from it. The first image that follows shows the related properties for that hierarchy and its level in the User Controlled Attribute Maintenance window. The second image that follows shows the hierarchy's level used in a view. It is used as the first level on rows. Subsequent levels drilled to are grouped by their respective Shipping Status member. This example shows Product Brand results summarized by each Shipping Status member.

## User Controlled Attribute Maintenance

📁 ⚙️ ⓘ ✕ ⬅️ ?

**General**

Dimension: Customer Parent

Attribute: User Controlled CPnt Shipping Status

Default Value: ?

Create Hierarchy: Yes

Hierarchy Name: Customer Prnt User Controlled Shipping Status

Level Name: Customer Prnt User Controlled Shipping Status

**Details**

Last Updated Date: 10/9/2020 11:23:09 AM

Last Updated By: Karen Shype

Pending Updates: No

Last Master Data Import Date: 11/16/2020 2:56:25 PM

Last Master Data Import By: Karen Shype

### ★ Weekly Numbers by Shipping Status

📁 ⚙️ ⓘ ✕ ⬅️ ?
Show All ⏪ ⏩ 1 to 30

View Filter: :: 📌 Customer Sold-To: Multiple ✕ +

	▼ Sales Wk 1 to Wk 38 2020	Sales Wk 1 to Wk 38 2019
<b>Customer Prnt User Controlled Shipping Status</b>		
<b>Same Day Shipping Available</b>		
Farm Fresh	\$1,324,063,156	\$1,263,397,415
Prime Grown	\$114,817,456	\$106,031,474
Home Cookin'	\$99,304,345	\$98,871,693
Private Label	\$47,003,060	\$44,020,069
SugarDrop	\$28,706,390	\$25,436,616
Farm Crisp	\$24,918,857	\$22,471,154
<b>Same Day Shipping Available Total</b>	<b>\$1,638,813,264</b>	<b>\$1,560,228,420</b>
<b>Ship Time &gt; 3 days</b>		
Farm Fresh	\$304,150,913	\$291,005,067
Prime Grown	\$170,914,254	\$154,699,268
Home Cookin'	\$157,085,591	\$146,053,688
Private Label	\$69,407,846	\$60,531,402
SugarDrop	\$42,072,229	\$38,469,296
Farm Crisp	\$30,843,655	\$28,653,841
<b>Ship Time &gt; 3 days Total</b>	<b>\$774,474,488</b>	<b>\$719,412,563</b>
<b>Back Order</b>		
Farm Fresh	\$425,369,894	\$405,343,509
Home Cookin'	\$122,486,905	\$117,661,640
Prime Grown	\$119,748,902	\$112,445,147
Private Label	\$58,977,694	\$56,635,279
SugarDrop	\$26,887,439	\$25,927,656
Farm Crisp	\$24,377,478	\$24,151,520
<b>Back Order Total</b>	<b>\$777,848,311</b>	<b>\$742,164,751</b>
<b>Special Order, Shipping Times Vary</b>		
Farm Fresh	\$222,052,584	\$210,238,988
Prime Grown	\$100,106,525	\$92,878,070
Home Cookin'	\$94,911,816	\$84,480,925
Private Label	\$49,384,386	\$47,343,041
SugarDrop	\$28,411,360	\$24,422,646
Farm Crisp	\$20,173,164	\$18,810,879
<b>Special Order, Shipping Times Vary Total</b>	<b>\$515,039,834</b>	<b>\$478,174,548</b>



## Using Master Data Import To Add New Dimension Key Values

Master Data Imports are primarily used to import data in User Controlled Attributes, whose set up is controlled through Stratum.Viewer's Used Controlled Attribute Maintenance. Another way you can use Master Data Import functionality is to add new dimension key values to Stratum. Doing that is useful during Budget or Forecasting activities when a new customer or product you need to budget / forecast for doesn't exist yet in your Corporate business system. For example, there's a new Customer Account that'll be activated soon or there's a new Product under development – and you want to account for them in Next Year's plan that you are setting up. You can include a row(s) with a key value for the dimension's new item(s) in a Master Data Import file. The import will add the new key values to Stratum for you, and then you can use Planning or Data Import functionality in Viewer to add budget / forecast data to the new items.

The following example shows a case for the UPC Global Number dimension. The user wants to add a couple User Controlled Attributes for the dimension and wants to add a new UPC Global Number to use while drafting next year's working plan. The view they'll use for planning is shown below before anything was added. The attributes get added with User Controlled Maintenance. Then, a Master Data Import is used to add data for the new attributes and add the key value for the new UPC Global Number.

★ Planning Updates - UPC GLObal Number						
View Filter: +						
Region	UPC Global Number	UPC Long Description	Next Yr Working Plan \$	Next Yr Working Plan #	This Yr Daily Sales \$	This Yr Daily Sales #
East	0 - 13800 - 30321 - 9	Frozen Lasagna Dinner			\$57,646,559	90,803
	0 - 13800 - 78934 - 9	Meatloaf, Frozen			\$51,896,801	86,216
	0 - 70606 - 02232 - 8	Pork Chops - Butterfly			\$30,219,613	68,454
	0 - 24000 - 12591 - 4	Peach Slcs LS 12oz BR*			\$29,974,775	98,808
	0 - 02749 - 25408 - 6	Asparagus			\$29,770,666	56,969
	<b>East Total</b>				<b>\$199,508,414</b>	<b>401,249</b>
West	0 - 13800 - 78934 - 9	Meatloaf, Frozen			\$13,903,680	22,257
	0 - 02749 - 99267 - 6	Cherries, Bing			\$13,524,573	27,516
	0 - 06403 - 92736 - 2	Orange Juice Conc.			\$11,763,265	25,952
	0 - 13800 - 30321 - 9	Frozen Lasagna Dinner			\$9,908,629	15,635
	0 - 70606 - 02041 - 2	Sirloin Tips - USDA Grade A			\$7,681,551	13,743
	<b>West Total</b>				<b>\$56,781,698</b>	<b>105,102</b>
<b>Grand Total</b>					<b>\$256,290,112</b>	<b>506,351</b>

Here's the view after the new User Controlled Attributes were created then added to the view. No data has been imported yet, so their default value of ? shows in the view for them.

★ Planning Updates - UPC GLocal Number								
View Filter: +								
Region	UPC Global Number	UPC Long Description	User Controlled - UPC Category	User Controlled - UPC Lead Time In Days	Next Yr Working Plan \$	Next Yr Working Plan #	This Yr Daily Sales \$	This Yr Daily Sales #
East	0 - 13800 - 30321 - 9	Frozen Lasagna Dinner	?	?			\$57,646,559	90,803
	0 - 13800 - 78934 - 9	Meatloaf, Frozen	?	?			\$51,896,801	86,216
	0 - 70606 - 02232 - 8	Pork Chops - Butterfly	?	?			\$30,219,613	68,454
	0 - 24000 - 12591 - 4	Peach Slcs LS 12oz BR*	?	?			\$29,974,775	98,808
	0 - 02749 - 25408 - 6	Asparagus	?	?			\$29,770,666	56,969
	East Total						\$199,508,414	401,249
West	0 - 13800 - 78934 - 9	Meatloaf, Frozen	?	?			\$13,903,680	22,257
	0 - 02749 - 99267 - 6	Cherries, Bing	?	?			\$13,524,573	27,516
	0 - 06403 - 92736 - 2	Orange Juice Conc.	?	?			\$11,763,265	25,952
	0 - 13800 - 30321 - 9	Frozen Lasagna Dinner	?	?			\$9,908,629	15,635
	0 - 70606 - 02041 - 2	Sirloin Tips - USDA Grade A	?	?			\$7,681,551	13,743
	West Total						\$56,781,698	105,102
Grand Total							\$256,290,112	506,351

Here's an import file that includes data for the attributes. There's also a row in the file containing the key value for the new UPC Global Number the user wants added to Stratum. It's in the last row.

New UPC GLocal Number & UCA Data - Saved				
File Home Insert Page Layout Formulas Data Review View Help ACROBAT				
I13				
	A	B	C	D
1	UPC Global Number	UPC Long Description	User Controlled - UPC Category	User Controlled - UPC Lead Time In Days
2	0 - 13800 - 30321 - 9	Frozen Lasagna Dinner	Frozen Prepared Meals	3
3	0 - 13800 - 78934 - 9	Meatloaf, Frozen	Frozen Prepared Meals	3
4	0 - 70606 - 02232 - 8	Pork Chops - Butterfly	Meat, Specialty	4
5	0 - 24000 - 12591 - 4	Peach Slcs LS 12oz BR*	Fresh Fruit	10
6	0 - 02749 - 25408 - 6	Asparagus	Fresh Vegetables	7
7	0 - 02749 - 99267 - 6	Cherries, Bing	Fresh Fruit	7
8	0 - 06403 - 92736 - 2	Orange Juice Conc.	Fresh Juice	7
9	0 - 70606 - 02041 - 2	Sirloin Tips - USDA Grade A	Meat, Specialty	4
10	0 - 85937 - 05360 - 4	Fresh Figs	Fresh Fruit	10
11				
12				
13				

A preview of the import displays in the Data Mapping - Master Data Import window once the user starts setting up an import with the previously shown file.

### Data Mapping - Master Data Import

Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option: Update

Validate
Configuration

Preview of rows 1 - 100

Dimension ▼	Ignore ▼	Attribute ▼	Attribute ▼
UPC Global Number ▼		User Controlled - UPC Category ▼	User Controlled - UPC Lead Time In Days ▼
<b>UPC Global Number</b>	<b>UPC Long Description</b>	<b>User Controlled - UPC Category</b>	<b>User Controlled - UPC Lead Time In Days</b>
0 - 13800 - 30321 - 9	Frozen Lasagna Dinner	Frozen Prepared Meals	3
0 - 13800 - 78934 - 9	Meatloaf, Frozen	Frozen Prepared Meals	3
0 - 70606 - 02232 - 8	Pork Chops - Butterfly	Meat, Specialty	4
0 - 24000 - 12591 - 4	Peach Slics LS 12oz BR*	Fresh Fruit	10
0 - 02749 - 25408 - 6	Asparagus	Fresh Vegetables	7
0 - 02749 - 99267 - 6	Cherries, Bing	Fresh Fruit	7
0 - 06403 - 92736 - 2	Orange Juice Conc.	Fresh Juice	7
0 - 70606 - 02041 - 2	Sirloin Tips - USDA Grade A	Meat, Specialty	4
0 - 85937 - 05360 - 4	Fresh Figs	Fresh Fruit	10

When the user submits the import for processing, a message displays about the new key value found in the import file. They click OK there then click OK in the subsequent message about proceeding with the import.

### Data Mapping - Master Data Import

Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option: Update

Validate
Configuration

Preview of rows 1 - 100

Dimension ▼	Ignore ▼	Attribute ▼	Attribute ▼
UPC Global Number ▼		User Controlled - UPC Category ▼	User Controlled - UPC Lead Time In Days ▼
<b>UPC Global Number</b>	<b>UPC Long Description</b>	<b>User Controlled - UPC Category</b>	<b>User Controlled - UPC Lead Time In Days</b>
0 - 13800 - 30321 - 9	Frozen Lasagna Dinner	Frozen Prepared Meals	3
0 - 13800 - 78934 - 9	Meatloaf, Frozen	Frozen Prepared Meals	3
0 - 70606 - 02232 - 8	Pork Chops - Butterfly	Meat, Specialty	4
0 - 24000 - 12591 - 4	Peach Slics LS 12oz BR*	Fresh Fruit	10
0 - 02749 - 25408 - 6	Asparagus	Fresh Vegetables	7
0 - 02749 - 99267 - 6	Cherries, Bing	Fresh Fruit	7
0 - 06403 - 92736 - 2	Orange Juice Conc.	Fresh Juice	7
0 - 70606 - 02041 - 2	Sirloin Tips - USDA Grade A	Meat, Specialty	4
0 - 85937 - 05360 - 4	Fresh Figs	Fresh Fruit	10

STRATUM.VIEWER
×

Your import file contains key value(s) that don't currently exist in Stratum for this dimension. When this data is imported, all the necessary Stratum Master Data will be created for you. If you have unexpected missing key values, verify your column mappings and the content of your import file before continuing.

OK



## When To Do An Update Vs. When To Do A Replace For Your Master Data Imports

There are two ways to configure your Master Data Imports. They can be set up to do an Update or a Replace, and the choice impacts the treatment of existing data. More information and examples follow to help you decide what type of import to use.

An **Update** is the more common type of import. It's the default configuration for Master Data Imports. An Update will update existing data and add any new data included in the import file.

A **Replace** is the less commonly used type of import. It clears existing data for **all** of the User Controlled Attributes that belong to the import's Target dimension then adds data from the import file to the applicable attributes.

- When might you need to do a Replace? You want to start over with a clean slate for a dimension. For example, you've done multiple imports for a dimension and want to start over with a fresh set of data or you mistakenly added new key values to the dimension and aren't using them.\* A replace deletes all data for all of the dimension's User Controlled Attributes and removes any unused dimension key values added by past Master Data Imports – unused key values are those that don't have any measure data. Key values that have measure data won't be removed by a Replace.
- Care should be taken when using a Replace since it removes data for **all** of a dimension's User Controlled Attributes. If there is existing data you don't want to lose, then set the import configuration to Update instead of Replace.
- Make sure the import file you use for the Replace includes all User Controlled Attributes for all key values you want updated for the dimension.

---

**\*Note:** To avoid adding new key values you don't need, make sure your import file only includes rows for the desired key values you want to update. See also the topic ['What Does "Import File Contains Key Values That Don't Currently Exist In Stratum" Message Mean?'.](#)

---

The following examples show an Update and a Replace to illustrate cases when you might choose to use each type of import.

### Update Example

This view has three new User Controlled Attributes for the Customer Priority level. Their default value of "?" displays because no master data has been imported yet. Data will be added with an Update type of Master Data Import.

★ UPC Global Number Sales vs Budget							
View Filter: +							
	Year			2019		2020	
Customer Priority	User Controlled CPrtY Contact Person	User Controlled CPrtY Service Level	User Controlled CPrtY Contact Email	Actual Sales \$	Budgeted Sales \$	Actual Sales \$	Budgeted Sales \$
A	?	?	?	\$3,670,039,141	66,337,197	\$3,393,809,671	62,085,172
B	?	?	?	\$2,756,096,439	49,050,526	\$2,543,360,159	45,642,175
C	?	?	?	\$914,566,908	15,017,988	\$847,432,441	14,081,410
Grand Total				\$7,340,702,488	130,405,711	\$6,784,602,271	121,808,757

Here's the import file showing data to be added.

	A	B	C	D
1	<b>Customer Priority</b>	<b>CPrty Contact Person</b>	<b>CPrty Service Level</b>	<b>CPrty Contact Email</b>
2	A	Maddie Suarez	Certified Partner	<a href="mailto:msuarez@abcbusiness.com">msuarez@abcbusiness.com</a>
3	B	Dellon Major	Professional Partner	<a href="mailto:dmajor@abcbusiness.com">dmajor@abcbusiness.com</a>
4	C	Barbara Hope	Standard Partner	<a href="mailto:bhope@abcbusiness.com">bhope@abcbusiness.com</a>
5				
6				
7				
8				
9				
10				

The import data is mapped to the appropriate attributes. Import Option is left at the default of Update.

**Data Mapping - Master Data Import**

Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option: **Update** Validate Configuration Preview of rows 1 - 100

Dimension	Attribute	Attribute	Attribute
Customer Priority	User Controlled CPrty ...	User Controlled CPrty ...	User Controlled CPrty ...
<b>Customer Priority</b>	<b>CPrty Contact Person</b>	<b>CPrty Service Level</b>	<b>CPrty Contact Email</b>
A	Maddie Suarez	Certified Partner	<a href="mailto:msuarez@abcbusiness.com">msuarez@abcbusiness.com</a>
B	Dellon Major	Professional Partner	<a href="mailto:dmajor@abcbusiness.com">dmajor@abcbusiness.com</a>
C	Barbara Hope	Standard Partner	<a href="mailto:bhope@abcbusiness.com">bhope@abcbusiness.com</a>

Here's the view after the import was finished. Attribute columns show their new data. The user can change any of this attribute data in the future, if needed, by doing another Update import. The images that follow this view show how another Update accomplishes that.

**★ UPC Global Number Sales vs Budget**

View Filter: **+**

			<b>Year</b>	<b>2019</b>		<b>2020</b>	
<b>Customer Priority</b>	<b>User Controlled CPrty Contact Person</b>	<b>User Controlled CPrty Service Level</b>	<b>User Controlled CPrty Contact Email</b>	Actual Sales \$	Budgeted Sales \$	Actual Sales \$	Budgeted Sales \$
A	Maddie Suarez	Certified Partner	<a href="mailto:msuarez@abcbusiness.com">msuarez@abcbusiness.com</a>	\$3,670,039,141	66,337,197	\$3,393,809,671	62,085,...
B	Dellon Major	Professional Partner	<a href="mailto:dmajor@abcbusiness.com">dmajor@abcbusiness.com</a>	\$2,756,096,439	49,050,526	\$2,543,360,159	45,642,...
C	Barbara Hope	Standard Partner	<a href="mailto:bhope@abcbusiness.com">bhope@abcbusiness.com</a>	\$914,566,908	15,017,988	\$847,432,441	14,081,...
<b>Grand Total</b>				\$7,340,702,488	130,405,711	\$6,784,602,271	121,808,...



The screenshot shows the Microsoft Excel interface. The ribbon at the top includes tabs for File, Home, Insert, Page Layout, Formulas, Data, Review, View, Help, and ACROBAT. The formula bar shows 'G17' and a function icon. The worksheet contains a table with the following data:

	A	B	C
1	<b>Customer Priority</b>	<b>CPty Contact Person</b>	<b>CPty Contact Email</b>
2	B	Andre Smith	<a href="mailto:asmith@abcbusiness.com">asmith@abcbusiness.com</a>
3			
4			
5			
6			

The status bar at the bottom indicates 'New for Priority B'.

### Data Mapping - Master Data Import

Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option: Update Validate Configuration Preview of rows 1 - 100

Dimension	Attribute	Attribute
Customer Priority	User Controlled CPty ...	User Controlled CPty ...
<b>Customer Priority</b>	<b>CPty Contact Person</b>	<b>CPty Contact Email</b>
B	Andre Smith	asmith@abcbusiness.com

★ UPC Global Number Sales vs Budget							
View Filter: +							
▼ Customer Priority	User Controlled CPty Contact Person	User Controlled CPty Service Level	▼ Year User Controlled CPty Contact Email	Budgeted Actual Sales \$	Budgeted Sales \$	Actual Sales \$	Budgeted Sales \$
A	Maddie Suarez	Certified Partner	msuarez@abcbusiness.com	\$3,670,039,141	66,337,197	\$3,393,809,671	62,337,197
B	Andre Smith	Professional Partner	asmith@abcbusiness.com	\$2,756,096,439	49,050,526	\$2,543,360,159	45,050,526
C	Barbara Hope	Standard Partner	bhope@abcbusiness.com	\$914,566,908	15,017,988	\$847,432,441	14,017,988
<b>Grand Total</b>				<b>\$7,340,702,488</b>	<b>130,405,711</b>	<b>\$6,784,602,271</b>	<b>121,337,197</b>



## Replace Example

This view shows all existing members (key values) for the Product Class level and two new User Controlled Attributes for the level. The default value of “%” displays for the attributes because no master data has been imported yet. Data will be added with a Master Data Import.

★ **Sales vs Returns Product Matrix**

View Filter: **RepBroker: Multiple**

Product Class	PClas Long Description	User Controlled PClas Department	User Controlled PClas Promotion Code	Actual Sales Amount	Actual Sales Return Amount	Sales After Returns
B	Branded	%	%	\$14,447,493,782	(\$230,163,732)	\$14,208,740,853
O	Other	%	%	\$789,115,326	(\$25,524,855)	\$771,040,175
P	Private Label	%	%	\$4,515,249,450	(\$45,701,994)	\$4,419,931,463
<b>Grand Total</b>				<b>\$19,751,858,558</b>	<b>(\$301,390,581)</b>	<b>\$19,399,712,491</b>

This import file is used for the import. The user overlooks the fact that the file includes key values R, E, and F that do not exist in Stratum yet – values the user does not mean to add to Stratum.




The screenshot shows an Excel spreadsheet with the following data:

	A	B	C
	Product Class	PClas Department	PClas Promotion Code
1			
2	B	Retail Stores	4732-850-7400b
3	O	Specialty Chains	9837-030-1192o
4	P	Direct To Customer	4487-000-2355p
5	R	Online Only Sales	5833-977-8007r
6	E	Emerging Markets	0076-212-6333e
7	F	Pop-Up Sales	1555-099-0052f
8			
9			
10			

A red rectangle highlights the data from row 5 to row 7. The status bar at the bottom indicates the active cell is G17 and the sheet is named 'Master Data for Prd Class'.

The user maps the data and proceeds with the import, still overlooking the new key values in the import file and that displayed in the mapping window. They also ignore an import validation message that tells them to check their import file if they did not intend to add new key values.

### Data Mapping - Master Data Import

Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option: Update


Validate
Configuration

Preview of rows 1 - 100

Dimension ▼	Attribute ▼	Attribute ▼
Product Class ▼	User Controlled PClas ... ▼	User Controlled PClas ... ▼
<b>Product Class</b>	<b>PClas Department</b>	<b>PClas Promotion Code</b>
B	Retail Stores	4732-850-7400b
O	Specialty Chains	9837-030-1192o
P	Direct To Customer	4487-000-2355p
R	Online Only Sales	5833-977-8007r
E	Emerging Markets	0076-212-6333e
F	Pop-Up Sales	1555-099-0052f

STRATUM.VIEWER

X



Your import file contains key value(s) that don't currently exist in Stratum for this dimension. When this data is imported, all the necessary Stratum Master Data will be created for you. If you have unexpected missing key values, verify your column mappings and the content of your import file before continuing.

OK

Click the Configuration tab to different data

Preview of rows 1 - 100

Product Class	User Controlled PClas ...	User Controlled PClas ...
Product Class	PClas Department	PClas Promotion Code
B	Retail Stores	4732-850-7400b
O	Specialty Chains	9837-030-1192o
P	Direct To Customer	4487-000-2355p
R	Online Only Sales	5833-977-8007r
E	Emerging Markets	0076-212-6333e
F	Pop-Up Sales	1555-099-0052f

Here's the view after the import was finished. Attribute columns show their new data. There are rows for the new key values. At this point, the user realizes their mistake of including new key values in their import file. Revising the import file and doing an import type of Replace will remove the unwanted values. The rest of this topic shows that Replace.

★ Sales vs Returns Product Matrix						
View Filter: <span>RepBroker: Multiple</span> <span>+</span>						
Product Class	PClas Long Description	User Controlled PClas Department	User Controlled PClas Promotion Code	Actual Sales Amount	Actual Sales Return Amount	Sales After Returns
B	Branded	Retail Stores	4732-850-7400b	\$14,447,493,782	(\$230,163,732)	\$14,208,740,853
E	?	Emerging Markets	0076-212-6333e			
E	?	Pop-Up Sales	1555-099-0052f			
O	Other	Specialty Chains	9837-030-1192o	\$789,115,326	(\$25,524,855)	\$771,040,175
P	Private Label	Direct To Customer	4487-000-2355p	\$4,515,249,450	(\$45,701,994)	\$4,419,931,463
R	?	Online Only Sales	5833-977-8007r			
Grand Total				\$19,751,858,558	(\$301,390,581)	\$19,399,712,491

The original import file is revised to remove the unwanted new key values. The rest of the content is left the same as used in the prior import.

AutoSave <span>Off</span> <span>Redo...</span> <span>Sa...</span> <span>Karen Farrelly</span> <span>KF</span>			
File Home Insert Page Layout Formulas Data Review View Help ACROBAT			
A14 <span>fx</span>			
	A	B	C
1	Product Class	PClas Department	PClas Promotion Code
2	B	Retail Stores	4732-850-7400b
3	O	Specialty Chains	9837-030-1192o
4	P	Direct To Customer	4487-000-2355p
5			
6			
7			
Master Data for Prd Class			

The Import Option is set to Replace in the mapping window. The Replace will clear all master data for all User Controlled Attributes, clear the new key values because they do not have measure data yet, and then import the attributes data for the key values in this iteration of the import file.

Data Mapping - Master Data Import			
Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.			
Import Option: <span>Replace</span>		<span>Validate</span> <span>Configuration</span>	Preview of rows 1 - 100
Dimension	Attribute	Attribute	
Product Class	User Controlled PClas ...	User Controlled PClas ...	
Product Class	PClas Department	PClas Promotion Code	
B	Retail Stores	4732-850-7400b	
O	Specialty Chains	9837-030-1192o	
P	Direct To Customer	4487-000-2355p	

Here's the view after the Replace was carried out. Only the desired Product Classes B, O, and P show up. Their User Controlled Attributes show the imported data. The unwanted key values R, E, and F were removed.

★ Sales vs Returns Product Matrix						
View Filter: <span>RepBroker: Multiple</span> +						
Product Class	PCLas Long Description	User Controlled PCLas Department	User Controlled PCLas Promotion Code	Actual Sales Amount	Actual Sales Return Amount	Sales After Returns
B	Branded	Retail Stores	4732-850-7400b	\$14,447,493,782	(\$230,163,732)	\$14,208,740,853
O	Other	Specialty Chains	9837-030-1192o	\$789,115,326	(\$25,524,855)	\$771,040,175
P	Private Label	Direct To Customer	4487-000-2355p	\$4,515,249,450	(\$45,701,994)	\$4,419,931,463
<b>Grand Total</b>				<b>\$19,751,858,558</b>	<b>(\$301,390,581)</b>	<b>\$19,399,712,491</b>

## Frequently Asked Questions (FAQ's)

## Can I Import Data Into More Than One Attribute At A Time?

Yes, if the User Controlled Attributes belong to the same dimension. Your import file can handle importing data for more than one attribute for the same dimension. In the following example, data is being imported into three attributes for the UPC Global Number dimension.

### Data Mapping - Master Data Import

Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option: Update

Validate
Configuration

Preview of rows 1 - 100

Dimension	Attribute	Attribute	Attribute
UPC Global Number	User Controlled UPC Lead Time in Days	User Controlled UPC Market Promotion Code	User Controlled UPC Seasonal Spend
<b>UPC Global Number</b>	<b>User Controlled UPC Lead Time in Days</b>	<b>User Controlled UPC Market Promotion Code</b>	<b>User Controlled UPC Seasonal Spend</b>
0 - 02749 - 99267 - 6	45	300	\$73.63
0 - 13800 - 30321 - 9	46	301	\$96.25
0 - 13800 - 78934 - 9	47	302	\$92.81
0 - 24000 - 12411 - 4	48	303	\$75.42
0 - 24000 - 12413 - 4	49	304	\$38.34
0 - 24000 - 12416 - 4	50	305	\$85.43
0 - 24000 - 12417 - 4	51	306	\$77.39
0 - 24000 - 12418 - 4	52	307	\$62.68
0 - 24000 - 12419 - 4	53	308	\$75.44
0 - 24000 - 12422 - 4	54	309	\$72.76
0 - 24000 - 12429 - 4	55	312	\$34.41
0 - 24000 - 12430 - 4	56	313	\$74.46
0 - 24000 - 12431 - 4	57	315	\$60.71

## Can I Import Data Into Corporate Controlled Attributes?


No. Data for Corporate Controlled Attributes always originates from your Corporate business systems and is stored in your Stratum.Server database.


## Is There A Limit To How Many User Controlled Attributes I Can Set Up?

Yes. You can add a maximum of 99 User Controlled Attributes per dimension.


## What Does “Import File Contains Key Values That Don’t Currently Exist In Stratum” Message Mean?

If your import file includes dimension key values that don’t currently exist in Stratum, you will get the following message. It tells you “Your import file contains key value(s) that don’t currently exist in Stratum”. Key values are unique identifiers of the members belonging to your Stratum dimensions.

- If you **did not** intend to add new key values for the dimension, then you need to cancel this import, remove rows containing the values from your import file, and try again. To cancel the import, click OK in this message and then click Exit  in the mapping window, which returns you to the Master Data Import list window. Nothing will be saved or processed for the import you were setting up
- If you **did** intend to add the new key value, then click OK and proceed with your import. See also [Using Master Data Import To Add New Dimension Key Values](#). That topic shows an example of an import where new key values were included to aid in business planning activities.



Here’s an example where a user didn’t intend to include a new key value. The dimension Product Group has four members 10, 11, 12, and 13. The user set up some User Controlled Attributes for the dimension and wants to import some data for them using the following import file. The last row was intended to be for existing key value 13, but there is a typo which makes the value there 133. Master Data Import will treat that value as a new key value. The user needs to correct the value to 13 and then try the import again.



	A	B	C	D
	Product Group	PGrp Long Description	User Controlled PGrp Marketing Code	User Controlled PGrp Sales Division
1				
2	10	Fresh Produce	9745	Grocery Chains
3	11	Canned Goods	9850	Food Services Industry
4	12	Fresh Meats	9746	Grocery Chains
5	133	Frozen Foods	9950	Food Services Industry
6				
7				
8				
9				
10				
11				
12				

Here's the key value message that showed when the import file with the typo displayed in the mapping window and the user clicked Validate. The mapping window also highlighted the applicable value in yellow.

### Data Mapping - Master Data Import

Preview of rows 1 - 100

Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option: Update ▼

Validate
Configuration

Dimension ▼	Ignore ▼	Attribute ▼	Attribute ▼
Product Group ▼		User Controlled PGrp Marketing Code ▼	User Controlled PGrp Sales Division ▼
<b>Product Group</b>	<b>PGrp Long Description</b>	<b>User Controlled PGrp Marketing Code</b>	<b>User Controlled PGrp Sales Division</b>
10	Fresh Produce	9745	Grocery Chains
11	Canned Goods	9850	Food Services Industry
12	Fresh Meats	9746	Grocery Chains
133	Frozen Foods	9950	Food Services Industry

STRATUM.VIEWER
×

Your import file contains key value(s) that don't currently exist in Stratum for this dimension. When this data is imported, all the necessary Stratum Master Data will be created for you. If you have unexpected missing key values, verify your column mappings and the content of your import file before continuing.

OK

Here's the mapping window after the typo was fixed in the import file and the user initiated a new import using that file. The import is about to be submitted for processing.

### Data Mapping - Master Data Import

Preview of rows 1 - 100

Use Submit The Master Data Import For Processing to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option: Update ▼

Validate
Configuration

Dimension ▼	Ignore ▼	Attribute ▼	Attribute ▼
Product Group ▼		User Controlled PGrp Marketing Code ▼	User Controlled PGrp Sales Division ▼
<b>Product Group</b>	<b>PGrp Long Description</b>	<b>User Controlled PGrp Marketing Code</b>	<b>User Controlled PGrp Sales Division</b>
10	Fresh Produce	9745	Grocery Chains
11	Canned Goods	9850	Food Services Industry
12	Fresh Meats	9746	Grocery Chains
13	Frozen Foods	9950	Food Services Industry

## What Happens If I Delete a Master Data Import That's Been Processed?

The definition for the import and its processing report will be deleted. The data that got imported when the import was processed remains in Stratum for you to use.

## What Should I Do If An Import File Size Exceeds Maximum Allowed Size?

A technical message from your browser telling you “the request entity is too large” or “content length exceeds the configured value” means that the size of your import file exceeds the maximum allowed file size. Files around the 28MB size or higher may result in this type of message and stop an import file upload.


A work around for this scenario is to split up your import into multiple, smaller files each with less rows and/or columns of data. Divide the data up into smaller files and import each file separately.

## Why Can't I Delete A Master Data Import?

Master Data Import definitions can only be deleted if they have a status of Completed or Error. An import that has a status of In Process cannot be deleted because Master Data Import is actively working with the import definition and import file.

## Why Did I Get An Email About Pending Changes For A User Controlled Attribute?

You will receive that type of email if related Stratum email settings identify you as a recipient for that type of notification. The email is sent out when someone adds a new User Controlled Attribute or changes an existing User Controlled Attribute. The email helps tell the recipients, typically your Stratum.Connector administrators, that changes exist and a Full process may be needed to update Viewer with the changes. The last image below shows the Parameter setting window in Connector where this type of email notification is controlled. The recipients, email subject, and email body text are set up in that window.





**Parameter Settings**

File Help

General **Emails** Key Errors Log Files

SMTP Server Name: silvonsmtp.silvon.com

Email From Address: silvon.connector@companyabc.com

Process Complete - Cube Available:

Email To Address: admin.user123@companyabc.com

Email Subject: 7.2 Connector Process Complete

Email Body: See the attached log for information on the Connector process.

Attach Process Log: Yes

Process Complete - Cube Locked:

Email To Address: admin.user123@companyabc.com

Email Subject: 7.2 Connector Process Complete - Cube Locked

Email Body: See the attached log for information on the Connector process.

Attach Process Log: Yes

Key Error Occurred:

Email To Address: admin.user123@companyabc.com

Email Subject: 7.2 Connector Process Key Error

Email Body: Key errors occurred during this process. Review the attached log.

Attach Key Error Log: Yes

**User Controlled Attribute Update Notification:**

Email To Address: admin.user123@companyabc.com

Email Subject: Stratum User Controlled Attribute - Pending Update for Viewer

Email Body: A change has been made to a Stratum User Controlled Attribute that may require a Full

## Why Didn't I Get An Email About A Master Data Import After It Finished Processing?

A few things can influence email delivery.

1. The Master Data Import may still be processing. Check its status in the [Master Data Import list window](#) or open its Processing Report to review processing stage details. See the topic [Review Processing Details For A Master Data Import](#).
2. An email address might not be specified for your user profile in Stratum.Viewer. An administrator can check your profile and verify it has an email defined for it.
3. The email may have been routed to your Junk email folder instead of your Inbox.

## Why Didn't The Import Configuration Window Show When I Uploaded An Import File?

Master Data Import makes configuration selections for you automatically when it picks up on and remembers selections from prior imports. Automatic configuration can save you steps in the import setup process.

You can open the import configuration window and make changes anytime from the [Data Mapping](#) preview by clicking Configuration.

### Data Mapping - Master Data Import

Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option:    Preview of rows 1 - 1

Dimension	Attribute
UPC Global	User Controlled UPC Seasonal
UPC Global	User Controlled UPC Seasonal
0 - 02749	\$73.63
0 - 13800	\$96.25
0 - 13800	\$92.81
0 - 24000	\$75.42
0 - 24000	\$38.34
0 - 24000	\$85.43
0 - 24000	\$77.39
0 - 24000	\$62.68
0 - 24000	\$75.44
0 - 24000	\$72.76
0 - 24000	\$34.41
0 - 24000	\$74.46
0 - 24000	\$60.71
0 - 24000	\$85.23
0 - 24000	\$77.46
0 - 24000	\$38.19
0 - 24000	\$95.01
0 - 24000 - 12440 - 4	\$72.75
0 - 24000 - 12441 - 4	\$62.80

#### IMPORT CONFIGURATION

**General**

Import Option:

Target Dimension:

**File Data**

Header Rows In File:

## Why Isn't A User Controlled Attribute Available In My Views?

A few things may cause a User Controlled Attribute not to show up in your views:

- The level for the attribute isn't included in the view. Verify the level has been added to the rows, columns, or view filter. You may also need to edit attribute relationship selections to select if for use in the view using the Edit Attribute Relationships window for the level.
- The attribute may have been disabled for use in administrator settings. Administrators can disable attributes from a Dimension window in Stratum.Viewer.
- The attribute is newly added and the pending updates to Viewer have not yet been processed. Additions or edits made in User Controlled Attribute Maintenance won't be reflected in Viewer until after the next Full process happens in Stratum.Connector.

## Why Were Some Mapping Selections Made For Me Automatically & Can I Change Selections?

Master Data Import makes mapping selections for you automatically when it picks up on and remembers selections from prior imports. For example, if you imported into a User Controlled Attribute for the Product dimension. The next time you do an import with a file that includes that dimension, automatic mapping will set the column for that dimension to Product in the mapping preview. Automatic mapping can save you steps in the import setup process.

You can change mapping selections using controls in the top two rows of the [Data Mapping](#) preview.

### Data Mapping - Master Data Import

Use this preview of your import file to tell us how to treat data during the import. Click the Configuration button if the preview layout doesn't match the import file layout or you want to map to different data than what's provided in the preview lists.

Import Option: Update Validate Configuration Preview of rows 1 - 100

Dimension	Attribute	Attribute	Attribute
UPC Global Number	User Controlled UPC Lead Time in Days	User Controlled UPC Market Promotion Code	User Controlled UPC Seasonal Spen
UPC Global Number	Cost Last Yr	User Controlled UPC Market Promotion Code	User Controlled UPC Seasonal S
0 - 02749 - 99267 - 6	Cost This Yr		\$73.63
0 - 13800 - 30321 - 9	User Controlled UPC Current List Price		\$96.25
0 - 13800 - 78934 - 9	User Controlled UPC Lead Time in Days		\$92.81
0 - 24000 - 12411 - 4	User Controlled UPC Market Promotion Code		\$75.42
0 - 24000 - 12413 - 4	User Controlled UPC Seasonal Spend		\$38.34
0 - 24000 - 12416 - 4	50	305	\$85.43
0 - 24000 - 12417 - 4	51	306	\$77.39
0 - 24000 - 12418 - 4	52	307	\$62.68
0 - 24000 - 12419 - 4	53	308	\$75.44

## Definitions

### Corporate Controlled Attribute

Attribute values are controlled either on the corporate side of things in Stratum.Server or using Stratum.Viewer's Master Data Import functionality. Both types can be used in the same way in Viewer. Values for Corporate Controlled Attributes originate from your Corporate business systems and are stored in your Stratum.Server database.

## Regular Measure Item

Regular measure items are items based on the measures in the Analysis Services database for your Stratum.Viewer environment.

Regular measure items can be created with or without time ranges, depending on the Time Range property for a view. If the Time Range property is Yes for a view, you can specify time ranges for its measure items. If the Time Range property is No, then time range functionality is disabled, but you can use time hierarchies in the view.

The regular measure items in the following view are based on Daily Sales measures and have a time range of Week 37 through 38 of 2014.

+ View Name: <i>Daily Sales by Customer Type</i>			
View Filter			
Customer Type	Ship-To Territory	Daily Sales Daily Sales Amount Wk 37 2014 to Wk 38 2014	Daily Sales Daily Sales Units Wk 37 2014 to Wk 38 2014
Class B Customer	Southwest	\$286,797	2,554
	South Central	\$317,063	2,734
	Gulf Coast	\$348,421	3,227
	Midlantic	\$400,396	3,779
	New England	\$529,373	4,516
	Great Lakes	\$189,547	1,741
	Great Plains	\$329,536	3,160
	Northwest	\$277,316	2,471
	Western Provinces	\$186,334	1,545
	Central Provinces	\$529,959	4,555
	Eastern Atlantic Provinces	\$596,137	5,502
Grand Total		\$3,990,880	35,784

## Target Dimension For Master Data Import

Master Data Imports have data mapping properties that define where imported data belongs after the import gets processed. Data can be imported into User Controlled Attributes of the dimension that has been selected as the Target Dimension for the Master Data Import.

## User Controlled Attribute

Attribute values are controlled either on the corporate side of things in Stratum.Server or using Stratum.Viewer's Master Data Import functionality. Both types can be used in the same way in Viewer. User Controlled Attributes are ones whose values originate from an Excel spreadsheet and become part of Stratum using Stratum.Viewer's Master Data Import functionality.\* Use Stratum.Viewer's User Controlled Attribute Maintenance functionality to define attributes, maintain attribute properties, create or remove hierarchies based on the attributes, or delete the attributes. In Connector, you can view their properties including seeing any hierarchy created from the attribute.

---

**\*Note:** User Controlled Attribute Maintenance functionality is only available for implementations running Stratum.Server on a Windows SQL server and that have a license for the Stratum Analyst Hub. It is not available for implementations running Stratum.Server on an IBM i Server.

---